2019-01-20

Framing resilience for river geomorphology: reinventing the wheel?

Gilvear, DJ

<http://hdl.handle.net/10026.1/13225>

10.1002/rra.3384

River Research and Applications

Wiley

All content in PEARL is protected by copyright law. Author manuscripts are made available in accordance with publisher policies. Please cite only the published version using the details provided on the item record or document. In the absence of an open licence (e.g. Creative Commons), permissions for further reuse of content should be sought from the publisher or author.

Framing resilience for river geomorphology: reinventing the wheel?

Ian C. Fuller^{1*}, Dave J. Gilvear², Martin C. Thoms³ & Russell G. Death¹

¹*Innovative River Solutions, School of Agriculture & Environment, Massey University,
Palmerston North, New Zealand I.C.Fuller@massey.ac.nz R.G.Death@massey.ac.nz*

²*School of Geography, Earth and Environmental Sciences, University of Plymouth,
Plymouth, Devon, UK david.gilvear@plymouth.ac.uk*

³*Riverine Landscapes Research Laboratory, Geography and Planning, University of New
England, NSW, 2351, Australia martin.thoms@une.edu.au*

*corresponding author

Abstract

Resilience is a well-used term in many disciplines, but inconsistently or little applied in river geomorphology, and river science. Recent developments in ecosystem ecology conceptualises resilience as comprising system resistance to, and recovery from, disturbance. The objectives of this paper are to consider how the concept of resilience in this bivariate form applies to river geomorphology, and provide a framework for bridging the disciplines of ecology and geomorphology, within the setting of river management using principles of resilience. River geomorphology sets the physical template upon which lotic processes act, thus understanding the resilience of this template is critical. The importance of consistency in defining principles of resilience thinking within the context of river science and management is important especially when promoting ecosystem resilience as a river

23 management goal. The application of resilience thinking with respect to river habitat is
24 provided through a series of examples from Australian and New Zealand river systems.

25

26 **Key words:** disturbance, river science, river habitat, river ecosystems, process-response

27

28 **Aim:**

29 How is the concept of resilience applied to river geomorphology, and what does a
30 geomorphologically resilient river look like?

31

32

33 **Introduction**

34 *Resilience defined*

35 Resilience, like the terms sustainability, heterogeneity and complexity, has multiple uses
36 and interpretations across many a range of disciplines (see Downes et al., 2013; Piégay et al.
37 2018). Different conceptualisations of a term can help to advance a field of study (Hodges
38 2008). Holling (1973; 1996) summarises resilience in ‘ecological’ and ‘engineering’ terms.
39 Engineering resilience focuses on resistance to disturbance, describing a system near an
40 equilibrium steady state. By comparison, ecological resilience focuses on the magnitude of
41 disturbance that can be absorbed before system structure and function change, and a new
42 regime ensues. The Resilience Alliance defines resilience in terms of system change, where:
43 resilience is the amount of change a system can undergo (its capacity to absorb disturbance,
44 or perturbation) and essentially retain the same function, structure and set of feedbacks
45 (Walker and Salt 2006). The concept of resilience has been increasingly recognised in
46 ecosystem ecology over the past five decades (Hill 1987; Holling 1973; Parsons et al. 2016;
47 Pimm 1984; Walker and Salt 2012; Westman 1978; Wohl 2014; 2016a; Thoms et al., 2018),
48 and is now undergoing a renaissance in a range of fields. However, it has not been widely
49 applied to river systems at a large, or arguably at consistent scales.

50 At the outset it is necessary to define our conceptualisation of disturbance and
51 perturbation; as any process resulting in or having the potential to effectively change or
52 disrupt the structure and / or function of a system. Perturbation in ecology has traditionally
53 been conceived as something short-term (e.g. a flood event), while disturbance inferred as
54 an event that was more destructive, rare and to all intents and purposes, unrecoverable
55 (Rykiel, 1985). However, this distinction is artificial: perturbation and disturbance are

synonymous (Rykiel, 1985), although the language of disturbance (e.g. pulse, press and ramp) has developed in ecology over the past three decades. When crossing disciplinary boundaries, it is important to be clear about the terms employed, and as such we define a disturbance as either a natural process (e.g. flood), or anthropogenic impact (e.g. pollution or structural control) affecting a system. This is consistent with the use of the terms in geomorphology, e.g. Gregory and Lewin (2014) argue that disturbance refers to any externally-driven perturbation.

The capacity of a system to absorb disturbance can be assessed at a range of biophysical, social and economic levels. For example, Parsons et al. (2016) identify fourteen attributes of resilience associated with river ecosystems, including ecological variability, ecosystem services, social capital, governance, feedbacks and thresholds. Thus, Parsons et al. (2016) argue that assessing the resilience of river ecosystems as a whole requires attention to the social, economic and biophysical attributes that confer resilience in river ecosystems. Similarly, Nimmo et al. (2015) recognise that the term ‘resilience’ in a policy sense in environmental management (e.g. Benson and Garmestani 2011). However Hodgson et al. (2015) argue the measurement of resilience is hampered by taking a broad view that embraces multiple processes, which are often conflicting. They suggest that resilience can be represented by a simultaneous consideration of resistance and recovery, acknowledging that a single metric is insufficient to capture the concept. This is analogous to the concept defined by Nimmo et al. (2015), as resistance-resilience, in which resilience is defined in the sense of capacity to recover from disturbance. Corenblit et al. (2015) also relate the concept of resilience to recovery from, and absorption of disturbance rather than resistance to disturbance (cf. Holling’s definition of ecological and engineering resilience).

An important distinction between resistance and resilience is provided by Meyer (2016), who recognises that resistance is related to whether, or the extent to which, system disruption will occur in response to disturbance; while resilience addresses disturbance and system recovery. When disturbed, systems both resist and recover from that disruption or perturbation, and resilience provides a means by which to capture this bivariate idea (Figure 1). Thus Hodgson et al. (2015) define resistance as the immediate impact of externally-driven disturbance on the state of a system, while recovery is the operation of intrinsic processes to restore the system towards, or back to, an equilibrium state. This ‘bivariate’ approach, which can be used to measure resilience, has recently been welcomed by Yeung and Richardson (2016) as providing an easily understandable representation of the concept, which can be used for ecosystem management. Hodgson et al. (2016) suggest that the study of resilience has suffered from a confusion of terms, metrics and definitions. In this paper, we align with recent suggestions posed in the literature and follow the bivariate approach to defining resilience as a single term proposed by Hodgson et al. (2015). It encompasses system resistance *and* recovery as applied to river geomorphology and in particular channel dynamics.

Figure 1

Objective: reframing for river geomorphology

The purpose of this paper is to consider how the concept of resilience in its bivariate form applies to river geomorphology, and in doing so provide a framework bridging the disciplines of ecology, geomorphology and engineering for use in the holistic management of river systems. Conceptualisation of resilience in these terms is required in order for resilience to be utilised as a way to manage, restore and rehabilitate rivers within the

102 context and challenges posed by global change. This is important because river
103 geomorphology sets the physical template for which lotic processes operate. To understand
104 river ecosystem resilience, the resilience of the physical template that structurally underpins
105 this ecosystem is critical. Loss of, or change in overall physical habitat may be as
106 detrimental to river ecosystem health as degraded water quality or quantity (Elosegi et al.
107 2010; Elosegi and Sabater 2013). The nature of river ecosystem structure and function, as
108 determined by river geomorphology, is a focal point of key frameworks in stream ecology.
109 These include the River Continuum Concept – RCC - (Vannote et al. 1980), Intermediate
110 Disturbance Hypothesis – IDH - (Connell 1978), Network Dynamics Hypothesis – NDH -
111 (Benda et al. 2004), Shifting Habitat Mosaic – SHM - (Stanford et al. 2005) and the Riverine
112 Ecosystem Synthesis – RES - (Thorp et al. 2006; Thorp et al. 2008). However, the extent to
113 which these frameworks provide an understanding of resilience is not necessarily explicit, or
114 even the focus of such schemes. To advance our knowledge of “healthy”, functioning river
115 ecosystems requires an understanding of the resilience of river geomorphology, but; what is
116 this, and how is it, or how should it be, defined? In the study of the resilience of river
117 geomorphology it is important also to acknowledge the role of biotic components within
118 fluvial ecosystems. River ecosystem resilience is a function of both geomorphology and the
119 collective of biota components. Biotic components respond to physical disturbances but
120 they also influence the magnitude of physical disturbances through various biotic
121 engineering processes. For example Trimble and Mendel (1995) identify the cow as a
122 geomorphic agent, responsible for widening stream channels under heavy grazing; while
123 Statzner et al. (2000) provide evidence for enhanced bed sediment erosion from crayfish
124 activity. Thus an understanding of geomorphic resilience is central to an understanding of
125 river ecosystem structure and functioning and vice-versa: if the physical habitat template is

not resilient, nor is the ecology. An example of some of the more frequently used terms in resilience and geomorphology are provided in Table 1.

Table 1

Resilience as a concept in geomorphology

The concept of resilience thinking is implicit in the study of geomorphology (Thoms et al., 2018). Principles of resistance and recovery underpin our understanding of the way geomorphic systems function via inter alia, equilibrium theory (cf. Thorn and Welford, 1994), and the role of extrinsic and intrinsic thresholds (Schumm, 1979), in governing the form and behaviour of landforms (cf. Coates and Vitek 1980). Many of these principles reinforce the paradigm of steady-state equilibrium, which has been a normative concept in geomorphology (Phillips, 2011); especially in stream restoration (e.g. Rosgen 1996). However, Phillips (2011) shows that ‘steady-state’ conditions are a point along an adjustment continuum, defined by the response of systems to disturbance. The concept of equilibrium in geomorphic systems is based on the notion of balance between process (input variables) and form. Thus when a geomorphic system is disturbed, there is a period of time - relaxation time - during which the system returns to a relative state of balance (Phillips 2014). In river systems, which are prone to disturbance from a range of variable drivers (e.g. storms generating floods and sediment), a truly steady state is unlikely because disturbance intervals tend to be shorter than relaxation time. Thus systems may not trend toward a steady state but rather a state of pseudo-equilibrium, which is normative in most river systems (Phillips 2011). River systems are characterised by constant, or at least

repeated, adjustment, tending towards, but never attaining a stable equilibrium. As such, they could be better viewed from an ecological resilience perspective (ie., a high capacity for reorganisation in response to changes in biophysical fluxes), than engineering resilience (cf. Holling 1996). More recently, Knight and Harrison (2014) suggested that Earth surface systems as a whole cannot be considered to exist at a steady state with regard to forcing variables driving their behaviour. This means that change, rather than stability, is the norm in geomorphology (Graf 1979) and specifically in river geomorphology (Gilvear et al., 2016). Change in river systems occurs as either a smooth transition, or an abrupt step-change; the timescale of analysis often determines how these changes appear (Schumm and Lichty 1965). Resilience can be construed as a measure of geomorphological behaviour over a range of spatial and temporal scales. Applying catastrophe theory as a model for describing space-time changes and Graf (1979) illustrated the potential for different behaviours of change in river systems. Graf (1979) hypothesised that a geomorphic system can be described by measures of force and resistance and response, and catastrophe theory indicates that changes taking place in the system can be described as a “cusp catastrophe” (p.20), occurring abruptly or gradually. Essentially this is another way of defining resilience. Here we define resilience as resistance and recovery of systems at a range of spatial and temporal scales in response to disturbance (Figure 1).

Resilience is therefore implicit to fluvial geomorphology, but often with little qualification of its precise meaning (although see Wohl 2016a and Thoms et al., 2018). It has been used to imply the degree of resistance to disturbance or perturbation from flood events, the maintenance of a stable channel form, and stabilisation of riparian structure, at a range of timescales (e.g. Gilvear 1999, Brooks and Brierley 2002, Kasai et al. 2004, Oldmeadow and Church 2006, Collins et al. 2012, , Jackson et al. 2015). Hydrological resilience was defined

173 by Botter et al. (2013) as buffering changes in external forcing. In contrast, Yuill et al. (2016)
174 and Hohensinner et al. (2014) relate resilience to recovery following disturbance, while
175 Buraas et al. (2014) set resilience alongside (in contradistinction to) resistance in the context
176 of channel response to floods. Newson and Large (2006) refer to resilience as a
177 characteristic of natural channels, but do not define the term as such, setting it alongside
178 river function and sensitivity.

179 From a geomorphological perspective, resilience, as a concept comprising both resistance
180 and recovery, is perhaps best understood in the geomorphological literature in terms of
181 sensitivity, as discussed recently by Wohl (2016a). Frequently used, geomorphic sensitivity
182 has been defined by Brunsden and Thornes (1979) as the relationship between the
183 frequency of disturbance (threshold exceeding) events and the recovery time, which is the
184 time it takes for a system to return to its pre-disturbance condition, in other words its
185 resilience (Phillips 2009). Downs and Gregory (1993) similarly connect sensitivity with the
186 ability of a system to recover from disturbance. Resilience has since been used in
187 conjunction with sensitivity by several authors, either implicitly or overtly (Harvey 2002;
188 Wittenberg and Newson 2005; Thompson et al. 2008; Fryirs et al. 2012; Bruschi et al. 2013;
189 Fryirs et al. 2015; Fryirs 2017). Rice et al. (2012) overtly recognise the relationship between
190 resilience as an ecological concept and geomorphological ideas of reaction, relaxation and
191 response time, which are all used to define system sensitivity. While Phillips and Van Dyke
192 (2016) argue that 'geomorphic resilience' relates to dynamical stability and is contingent on
193 how recovery is conceived or defined. This definition refers to the capacity to recover to or
194 towards a pre-disturbance state, with systems better able to recover being more resilient.
195 This definition of a resilient system was also recognised by Wohl (2014), who tracked the
196 adoption of ecological concepts of resilience, sustainability and ecological integrity by fluvial

geomorphologists since 2000, in attempts to characterise river health. Resilience is becoming recognised by many as a desirable working concept in river management, e.g. Wohl (2016a), but exactly what is being desired when fluvial geomorphologists speak of the need to improve resilience? Does this mean to improve sensitivity and propensity for change; or enhance recovery following disturbance; or enhance resistance to minimise disturbance in the first place? Downs et al. (2013) argued that the most natural (least modified) reaches of the Santa Clara River, California, were the most morphodynamically resilient, since these stretches, while responding to floods by channel widening, lacked sufficient sensitivity to generate a persistent and recognisable response. This is in contrast to more modified reaches, which suppress morphodynamic sensitivity, but which enhance process sensitivity due to greater sediment transport capacity (Downs et al. 2013). A similar situation has been observed in New Zealand by Fuller and Basher (2013), where the largest recorded flood in the upper Motueka River (Good Friday, April, 2005) resulted in minimal channel planform change due to rock-lined banks, but enhanced sediment transfer, and in fact bed degradation, in the narrowed river corridor. As Downs et al. (2013) point out, the potential for morphodynamic sensitivity in such cases is very high should embankments or (in the case of the Santa Clara River) grade control structures fail during a flood event that exceeds design capacity. Resilience in these engineered rivers is thus forced, rather than inherent as a system property. In this paper we discuss the application of a reframed view of resilience to river geomorphology. We consider how geomorphic resilience, together with thresholds and trajectories can be conceptualised as part of this application. This leads the way to discussing what a geomorphologically resilient river may look like and how rivers should be managed for resilience, particularly in an era of global change. Our discussion is amplified by the use of discrete case studies for illustration.

221

222 **Resilience applied to river geomorphology**

223 River morphology is influenced by a range of variables, operating at multiple scales
224 (Schumm, 1998). These include the flow regime (the magnitude and variability of
225 discharges, which relate to the prevailing climate regime, and the history of flows), slope,
226 sediment supply and the textural character of the sediment (related to catchment geology),
227 riparian vegetation and bank composition (e.g. alluvium or bedrock). These variables
228 provide boundary conditions that determine how river channels respond to disturbance,
229 such as a large flood or tectonic activity (e.g. the 2010-2011 Christchurch earthquake
230 sequence in New Zealand resulted in base level change and lateral spreading impacting the
231 Avon River –see Fuller et al. 2016). The combination of variables determining river
232 morphology vary continuously, both spatially and temporally, producing a continuum of
233 channel forms in a catchment (Schumm 1977; Fryirs and Brierley 2013). Within a particular
234 river reach, changes to the assemblage and composition of morphological units, e.g. bars,
235 riffles, pools and runs, and changes in the textural character of the river bed substratum in
236 response to floods are determined by the initial sediment texture and channel morphology
237 (Thorp et al. 2006; Poole 2010; Elosegi and Sabater 2013). These scales – the morphological
238 unit and substrate scale – represent critical physical habitat for in channel biota, and the
239 health of river ecosystems. The concept of resilience is best applied to river geomorphology
240 at these scales, recognising that river character / type is characterised by a particular
241 assemblage of these units (Fryirs and Brierley, 2013). At the reach scale or morphological
242 unit scale, resilience is thus the propensity of a river to retain its characteristic assemblage
243 of channel features / units following disturbance. This notion is central to the Shifting
244 Habitat Mosaic Concept (SHMC) of Stanford et al., (2005), which recognises that different

fluvial units may have different geomorphic resiliences. In effect, this is the capacity of the river geomorphology to both resist and recover from disturbance, or ‘absorb’ disturbance without substantial change to overall form (Figure 2) at this scale. In (pseudo-) equilibrium terms, this has been recognised as dynamic equilibrium (Hack 1975).

Figure 2.

Geomorphic resilience, thresholds & trajectories

The capacity of a river to absorb (resist and recover from) disturbance is connected to geomorphic thresholds in discrete river reaches. River channel changes occur when thresholds relating to stream power, or flow regime and sediment regime are exceeded (Schumm 1979). Where a river reach lies close to a geomorphic threshold it is primed for change (i.e. it is sensitive to change), which is triggered by disturbance (Brewer and Lewin 1998, and see Schumm 1969; 1979). In such a situation, resistance to change is low, and channel adjustment occurs. Recovery to a disturbance may be rapid (Figure 2), with characteristic morphological units quickly re-established – here vegetation colonisation and development may also play a role (e.g. Dollar et al. 2007; Caruso et al. 2013) and provide a link with riverine plant ecology. The potential relationship between resistance and recovery in generating system resilience is shown in Figure 3, where various resilience trajectories are described. The resilience trajectory of a reach is dependent upon its sensitivity to disturbance, and in turn conditioned by its proximity to a threshold (Brunsden and Thornes 1979; Brunsden 2001). A disturbance that fails to exceed a threshold will result in no change in unit structure, river morphology or physical habitat. In this situation resilience is ‘static’

(cf. Figure 3c) and may describe the behaviour of river geomorphology to small, frequent floods. These smaller (within-channel) floods, which can occur c.14-30 times a year in humid temperate environments (Harvey et al. 1979) are critical for maintaining suitable habitat and ecological integrity. These flow events prevent substratum armouring, fine sediment accumulation and excessive periphyton proliferation that can cause cascading trophic changes and reduce ecological condition (Clausen and Biggs 1997; Poff et al. 1997; Death 2008; Lessard et al. 2013), despite having little effect on reach-scale geomorphology. By comparison, larger floods represent potentially greater disturbance, which can be catastrophic in nature (Fuller 2008; Death et al. 2015). Where recovery is rapid, resilience can be considered as 'steady state' (Figure 3a), because the system has absorbed the disturbance and returned to its pre-flood condition (i.e. channel form and assemblage of morphological units). In this case, resistance and recovery are balanced, and since the system absorbs the disturbance, this could be considered as resilience in its classic sense. Based on an assessment of gauged reaches, Phillips and Jerolmack (2016) argue that channels adjust their shape so that floods only slightly exceed sediment transport thresholds, which they suggest is a mechanism of self-organisation. As such, steady-state resilience could be considered as an endemic trait in river geomorphology. In contrast, a catastrophic response to flooding can also occur, resulting in complete transformation of reaches (e.g. Schumm and Lichty 1963, Hauer and Habersack 2009, Thompson and Croke 2013). The notion of steady-state or static resilience does not apply in such circumstances. Although this is timescale-dependent (cf. Schumm and Lichty, 1965), and raises the possibility that resilience in geomorphology must be viewed across multiple timescales (Thoms et al., 2018), albeit spatially at the reach / morphological unit scale. However, this need not necessarily imply that such rivers are not resilient. Phillips (2009) argues that if the

pre-disturbance state of a system is not restored, a system can be construed as non-resilient, or having low resilience. Nevertheless, resilience is itself dynamic (Figure 3b), where progressive change occurs in a system adjusting to new boundary conditions, as has been discussed in Schumm's (1969) model of channel metamorphosis, e.g. a progressive increase in discharge and bed load may increase channel width, width:depth ratio, meander wavelength and channel gradient, while reducing sinuosity. In the East Coast Region of New Zealand, where land-use change has rendered catchments prone to erosion, rivers have been more dramatically transformed from narrow, single-thread systems to rapidly aggrading multi-thread rivers (Page et al. 2007). While in many cases such a change proceeds over several decades, centuries, or even millennia, in one particular East Coast river, the Raparapaririki, the system was transformed within a decade (Tunncliffe et al. 2018). The transformation of this channel was associated with a major storm event in 1988, and the shift in channel type provides a contemporary example of meta-stable resilience (Figure 3d), which Werritty (1997) referred to as responsive behaviour. Here, steady-state resilience would be categorised as robust. In resilience thinking, robustness would be expected to equate to resilient channel behaviour. However, meta-stable resilience is, arguably, not resilience in the conventional sense because the disturbance has not been absorbed, the system has not recovered, nor resisted, but responded to the disturbance, crossed critical geomorphic thresholds and been transformed to a new channel type, with the prospect of recovery unlikely at a centennial scale (Tunncliffe et al. 2018). Resilient rivers are thus robust rivers using Werritty's (1997) definitions. Transformative (responsive) change occurs in rivers sensitised to disturbance, sitting close to thresholds (Brewer and Lewin 1998), or in rivers that are subject to wholesale regime change (e.g. Page et al., 2007,

Tunncliffe et al., 2018). Case study 1 provides an example of different trajectories (i.e. directions) of river channel change in the Lower River Murray, South Australia.

Figure 3.

Case Study 1.

The relationship between disturbance frequency, rate of recovery and amplitude of response is important, as it contributes to understanding resilience in the context of river geomorphology (Figure 4). It is important to note that the resulting system dynamics can be considered resilient regardless of how dynamic they are. Highly dynamic rivers, sensitive to small floods, which absorb disturbance and do not experience changes in the assemblage of unit morphologies exhibit robust behaviour (Werritty, 1997), are resilient as moderately dynamic or steady state rivers. In this case, each adjusts to the frequency of disturbance, amplitude of response and rate of recovery that are inherited from the catchment boundary conditions.

Figure 4.

Geomorphologically resilient rivers

What do geomorphologically resilient rivers look like? How should rivers be managed for resilience? A range of river types and dynamics can be considered resilient, especially where disturbance is absorbed and river form retained or recovered. However, not all resilient

337 rivers are necessarily healthy rivers, particularly where river management has sought to
338 maintain a stable channel form with naturally occurring change and propensity for that
339 change being seen as undesirable (Raven et al. 2010; Fuller and Basher 2013). Healthy rivers
340 are those that manifest diversity and complexity of expected form (Wohl, 2016b). These
341 'messy rivers' have a natural capacity to adjust in response to disturbance, which makes
342 them resilient. The range of natural capacity for adjustment will be dependent upon the
343 character of each river system (cf. Fryirs and Brierley, 2013). As such, both dynamic and
344 non-dynamic river types in their natural state are resilient to the natural range of
345 disturbance (i.e. floods) in their catchment. In its unaltered condition, a river responds with
346 resilience to even the largest floods, because its natural form and character will adjust and
347 recover over time. The problem for river management is that many rivers are now no longer
348 in a natural catchment setting. The following discusses application of the theoretical
349 understanding of resilience as a concept in fluvial geomorphology to inform and improve
350 river management.

352 *Resilience and river management*

353 Traditional river management deliberately homogenises reaches, reducing form
354 complexity and habitat diversity (Wohl 2016a). The end product is robust and insensitive
355 rivers with a largely fixed form (Fuller et al. 2012; Fuller and Basher 2013), at least over
356 short and medium timescales until a "catastrophic flood" occurs. These rivers have
357 suppressed morphodynamic sensitivity (Downs et al. 2013) and could be argued to be highly
358 resilient, because there is no morphological response to most disturbances. But resilience in
359 these systems is largely a product of resistance, since change, and therefore recovery, is

often minimal. In fact such reaches lack the capacity to adjust naturally to disturbance, require large-scale investment to maintain their modified form and are vulnerable to wholesale change in the event of infrastructure failure (Downs et al. 2013, Fuller and Basher 2013) and are then very expensive to reinstate. Such forced resistance is not conducive to river health, since habitat diversity is severely curtailed and the shifting habitat mosaic effectively stabilised. Furthermore, there is a significant risk of major geomorphic change in these forced resilient systems, should engineering fail (Downs et al. 2013). A critical debate here is the respective resilience, especially in a period of environmental change, of heavily managed rivers and more natural counterparts. An example of resilience and managing rivers is provided in Case Study 2.

Case Study 2

Rehabilitating for resilience

River rehabilitation focused on resilience is to increase the capacity for recovery. This concerns both the improvement of the recovery in time and space, and minimising the likelihood of large-scale system change to a new state or costly periodic management interventions such as dredging. A resilient river geomorphology is not characterised by zero change or static geomorphology, but by disturbance, response and recovery, and, inevitably, a degree of complexity (Wohl 2016a). To allow for this, most engineered rivers require 'room to move'. This concept has been advocated in terms of an 'erodible river corridor' (Piégay et al. 2005); 'freedom corridor' (Biron et al. 2014, Buffin-Bélanger et al. 2015); and 'protected mobility corridor' (Choné and Biron 2016). It entails working with nature and

respecting geomorphic diversity (Brierley and Fryirs 2009). Importantly, permitting movement means allowing for lateral mobility or channel migration, which are important for maintaining and redistributing sediment (Rinaldi et al. 2013) and sustaining resilience within the system. This in turn connects with physical habitat, because redistribution of sediment means the riverbed is being turned over and pool-riffle units and bars, which develop or are maintained as sediment is redistributed, provide important biotopes and habitat, enhancing biodiversity (Milan et al. 2010; Michalková et al. 2011; Garcia et al. 2012). At a finer scale, mobilisation of riffle sediments is particularly important as this prevents clogging by fine sediment, which is detrimental to ecology – indeed here low resistance to disturbance provides habitat resilience to elevated suspended sediment loading from disturbed catchments. Bank erosion itself is also of benefit to the functioning of river ecosystems (Florsheim et al. 2008) and is a key channel adjustment mechanism during flood disturbance events (Fuller 2008, Phillips and Jerolmack 2016). Indeed, bank erosion allows rivers to increase their capacity as floods become larger and more frequent. Bank erosion linked to lateral migration of meanders also leads to the development of point bars that provide niche habitats for some plants and animal species, and is thus a component of river resilience that should be biologically valued. This process relates to the shifting habitat mosaic, which is an established concept in the functioning of natural ecosystems (Stanford et al. 2005)

Revegetation is important for the rapid recovery of fluvial surfaces to the pre-disturbance state following perturbation (Gurnell 2014, Gurnell et al. 2016). In this sense healthy, resilient riverine landscapes are those which supply pioneer species via hydrochory (e.g. Terera et al. 2015). Without such a process, change from meandering to wandering and wandering to braided river morphologies is more likely, given the stabilising influence of

revegetation. In turn these planform changes pose challenges for river management, as the erodible river corridor width increases without the stabilising and / or limiting effect of revegetation. However, in New Zealand, recent invasion of river corridors by exotic weed species including willow, lupin, gorse and broom has inhibited natural river dynamics in historically active gravelly rivers (native vegetation grows much more slowly than exotic weeds). For example, the Waitaki River, a naturally active braided river in North Otago, has been stabilised significantly by invasive riparian vegetation (Caruso et al. 2013). This vegetation has altered channel and bar dynamics, and associated river habitat and in this case choking of the active channel by invasive vegetation has arguably reduced resilience. To illustrate this point, the Kiwitea Stream in the North Island of New Zealand responded catastrophically to a 100 year annual recurrence interval (ARI) flood in 2004 (Fuller 2008). The reason for this catastrophic response lay in the over-narrowed channel, lined by extensive exotic vegetation (Fuller and Heerdegen 2005). In much the same way as the River Tay, Scotland, responded to a shift in flood regime, the river in this narrowed form was unable to accommodate the 100 year ARI event. The river morphology and attendant river habitat was transformed (Figure 5). Subsequent river engineering has reduced active channel width, but not to the same degree as prior to 2004. The outcome is a wider river corridor, with a diversity of habitat that is more resilient, since both disturbance and recovery are now allowed for. In this example, the resilience capacity has been improved relative to the 1995 channel and the likelihood of subsequent catastrophic transformation been reduced.

Figure 5.

430

431 *Prospect*

432 Rivers will be exposed to greater frequencies and magnitudes of disturbance with future
433 climate change and predicted increases in frequency and magnitude of extreme events (e.g.
434 Donat et al., 2016). This change can be considered as pulse, ramp or press in nature,
435 following Lake (2000). Changing climate is likely to increase flood magnitude and
436 storminess, which equates to increasing pulse disturbance (Phillips and Van Dyke 2016); as
437 recently seen in Haiti and North Carolina with Hurricane Matthew in October 2016 (Figure
438 6). However, increased frequency and magnitude of floods constitutes a ramp disturbance,
439 as the strength of the disturbance increases over time (Lake 2000) (Figure 7). Ultimately,
440 these changes may result in a press disturbance, where disturbance regime changes. In
441 sensitive systems, press disturbance results in permanent change in boundary conditions,
442 responsive change takes place, and resilience changes (cf. meta-stable resilience, Figure 3).
443 Since geomorphic sensitivity and resilience relate to the magnitude and frequency of
444 disturbance (Brunsden and Thornes 1979, Brunsden 2001, Phillips and Van Dyke 2016), the
445 relationship between disturbance and response will potentially change as frequency and
446 magnitude change. Schumm (1998) recognised that sensitivity adjusts over space and time,
447 and Fryirs (2013) noted that systems can become more or less sensitive to future
448 disturbances. In turn, a change in sensitivity may effect a change in resistance to
449 disturbance, and thus resilience (Figure 7). In each of the scenarios depicted in Figure 7,
450 resilience is likely to change. It is difficult to predict whether, as Fryirs (2013) suggests, some
451 systems may become more resilient, while others more sensitive. The outcome will be
452 dependent on the magnitude-frequency of disturbances and the inherent characteristics
453 and sensitivity of the system. Where reaction and relaxation time exceed the frequency of

disturbances, the system is unable to recover and a ramped response is likely (Figure 7). In such a scenario, resilience, i.e. the ability to absorb disturbance, may be compromised and change in river geomorphology (unit assemblage and channel form) is likely.

Figure 6.

Figure 7.

There is a need to allow for rivers to adjust to changing sediment flux and flow conditions to ensure properly functioning, suitably complex, resilient systems are maintained. Resilience or river sensitivity is not static. Trying to keep river channels as they are today, while the driving forces and boundary conditions that are responsible for these channels and their assemblage of morphological units change within the catchment is not tenable and does not foster resilience in river geomorphology. Instead, change must be anticipated, erosion permitted, adjustment allowed, and complexity in river form, which engenders diversity of river habitat and healthy river ecosystems (Wohl 2016a) must be recognised in framing resilience for river geomorphology. The *rate* of change can be mitigated by strategic and targeted catchment management, taking into account catchment connectivity. For example, reforestation can help reduce some flood peaks and certainly help reduce sediment flux by reducing slope erosion. These measures may slow down the rate of change in river geomorphology, but cannot, ultimately prevent change altogether. Managing for complexity and resilience at a reach-scale, so that adjustments can take place and disturbance absorbed, can be facilitated or enhanced by an holistic approach to catchment management. This requires an understanding of resilience at a larger spatial scale, a

‘network resilience’, which recognises that connectivity within the contributing catchment is fundamental to maintaining the natural scope of river adjustments and response to perturbation (e.g. Fryirs 2013). Where connectivity is disrupted at a catchment scale, resilience at a reach-scale (and ultimately patch-scale) may be compromised, because the flow of water and sediment which enables reaches to absorb, resist or recover from disturbance is compromised. Resilient river geomorphology is responsive to change and connected with the larger catchment. Catchment connectivity is thus a fundamental component underpinning resilience in river geomorphology.

Some river geomorphologies are naturally adjusted to high magnitude and frequency flood events. Monsoonal river systems have always experienced large floods and their resilience is unlikely to change in response to increased disturbance, in fact high magnitude floods have increased in recent decades (Kale et al. 1997) but without undue effects on river morphology (Macklin et al. 2012, Muhammad et al. 2013). Large lowland river systems have similarly been structured by large floods and are unlikely to show major geomorphological response to big floods in future (e.g. Croke et al. 2013). As such, these rivers can be construed as being resilient, even in an era of global change. However, Fryirs et al. (2015) suggest that while one such river (Lockyer Creek, which is typical of many southeast Queensland (Australia) systems in having a high flash flood index) appears to have been geomorphically resilient to large floods since European settlement (ca. 250 years), there remains a need for work to assess whether the resilience of such a system will continue in the same form, with increasing frequency of extreme floods projected with forecast climate change. Resilience in the past, does not necessarily ensure resilience in the future. The exact nature of changes in magnitude or frequency or both are likely to be critical in controlling future geomorphic trajectories. Fryirs (2013) calls for a better understanding of river

sensitivity (aka resilience) by generating empirical data that can measure it, such as understanding the character and behaviour of a reach to assess the frequency and nature of adjustment, which is an approach to assessing geomorphic sensitivity outlined by Reid and Brierley (2015). The greatest challenge to understanding and forecasting resilience is the non-stationarity of river systems, and the nested hierarchy of sensitivity and resilience forces acting in a system in both space and time (Fryirs 2017) along with the length of record of change needed. Accordingly sensitivity / resilience of flood regimes to climate change is strongly contingent on specific environmental and historical context (Knox 2000, Phillips and Van Dyke 2016). Fundamentally, the concept of river geomorphology resilience and effective prediction of future resilience of river geomorphology must recognise the history of a river system. This contextualises both the present and future morphological structures and processes. Examination of river system response and recovery to past disturbance is a direct way of assessing resilience (Phillips 2009), and should be a priority to advance the understanding of the physical template of river habitat. Framing resilience of river geomorphology begins to meet these challenges, by advocating a consistency in defining principles of resilience thinking within the context of river science and management, and understanding how a geomorphologically resilient river behaves.

Conclusions

Resilience in river science recognises that geomorphologically resilient rivers may be highly dynamic, or exhibit classic stability (Figure 4). Resilience may be manifest in several ways, dependent upon the nature and frequency of disturbance and the sensitivity of the river system (Figure 1). Enhancing resilience may require an improvement of geomorphic

sensitivity and propensity for change in the case of over-engineered rivers; or facilitating recovery following disturbance; or resistance to minimise disturbance in the first place. This depends on the nature of the system and its trajectory. River channel change is the norm (Raven et al. 2010) and this should be incorporated into understanding resilience. Ultimately, the least impacted by people and more connected the channel is with its floodplain and catchment, the more resilient it can be expected to be. Changing boundary conditions, like ensuring connectivity, will allow for changes to be worked through into a river which is both sensitive to and in equilibrium with the flux of water and sediment supplied by its catchment.

Acknowledgements

We thank the reviewers tasked with reviewing this manuscript for their helpful and constructive reviews and state that the authors declare no conflict of interest. This manuscript arises from a resilience workshop co-hosted in December 2015 by Massey University and the Leibniz Institute of Freshwater Ecology and Inland Fisheries, Berlin, whose support in kind is acknowledged, as are the efforts of Dr Kris van Looy.

References

- Benda L, Poff NL, Miller D, Dunne T, Reeves G, Pess G, Pollock M. 2004. The network dynamics hypothesis: how channel networks structure riverine habitats. *BioScience* 54:413-427.
- Benson MH, Garmestani AS. 2011. Can we manage for resilience? The integration of resilience thinking into natural resource management in the United States. *Environmental Management* 48:392-399.
- Biron PM, Buffin-Bélanger T, Larocque M, Choné G, Cloutier C-A, Ouellet M-A, Demers S, Olsen T, Desjarlais C, Eyquem J. 2014. Freedom Space for Rivers: A Sustainable Management Approach to Enhance River Resilience. *Environmental Management* 54:1056-1073.

550 Botter G, Basso S, Rodriguez-Iturbe I, Rinaldo A. 2013. Resilience of river flow regimes. *Proceedings*
551 *of the National Academy of Sciences* 110:12925-12930.

552 Brewer PA, Lewin J. 1998. Planform cyclicity in an unstable reach: complex fluvial response to
553 environmental change. *Earth Surface Processes and Landforms* 23:989-1008.

554 Brierley G, Fryirs K. 2009. Don't Fight the Site: Three Geomorphic Considerations in Catchment-Scale
555 River Rehabilitation Planning. *Environmental Management* 43:1201-1218.

556 Brooks AP, Brierley GJ. 2002. Mediated equilibrium: the influence of riparian vegetation and wood
557 on the long-term evolution and behaviour of a near-pristine river. *Earth Surface Processes and*
558 *Landforms* 27:343-367.

559 Brunsden D. 2001. A critical assessment of the sensitivity concept in geomorphology. *Catena* 42:99-
560 123.

561 Brunsden D, Thornes J. 1979. Landscape sensitivity and change. *Transactions of the Institute of*
562 *British Geographers*:463-484.

563 Bruschi VM, Bonachea J, Remondo J, Gómez-Arozamena J, Rivas V, Méndez G, Naredo JM, Cendrero
564 A. 2013. Analysis of geomorphic systems' response to natural and human drivers in northern Spain:
565 Implications for global geomorphic change. *Geomorphology* 196:267-279.

566 Buffin-Bélanger T, Biron PM, Larocque M, Demers S, Olsen T, Choné G, Ouellet M-A, Cloutier C-A,
567 Desjarlais C, Eyquem J. 2015. Freedom space for rivers: An economically viable river management
568 concept in a changing climate. *Geomorphology* 251:137-148.

569 Buraas EM, Renshaw CE, Magilligan FJ, Dade WB. 2014. Impact of reach geometry on stream channel
570 sensitivity to extreme floods. *Earth Surface Processes and Landforms* 39:1778-1789.

571 Caruso BS, Pithie C, Edmondson L. 2013. Invasive riparian vegetation response to flow regimes and
572 flood pulses in a braided river floodplain. *Journal of environmental management* 125:156-168.

573 Choné G, Biron PM. 2016. Assessing the Relationship Between River Mobility and Habitat. *River*
574 *Research and Applications* 32:528-539.

575 Clausen B, Biggs B. 1997. Relationships between benthic biota and hydrological indices in New
576 Zealand streams. *Freshwater Biology* 38:327-342.

577 Coates D, Vitek J. 1980. Perspectives on geomorphic thresholds. George Allen & Unwin, London.

578 Collins BD, Montgomery DR, Fetherston KL, Abbe TB. 2012. The floodplain large-wood cycle
579 hypothesis: A mechanism for the physical and biotic structuring of temperate forested alluvial
580 valleys in the North Pacific coastal ecoregion. *Geomorphology* 139–140:460-470.

581 Connell JH. 1978. Diversity in tropical rain forests and coral reefs. *Science* 199:1302-1310.

582 Corenblit D, Davies NS, Steiger J, Gibling MR, Bornette G. 2015. Considering river structure and
583 stability in the light of evolution: feedbacks between riparian vegetation and hydrogeomorphology.
584 *Earth Surface Processes and Landforms* 40:189-207.

585 Croke J, Todd P, Thompson C, Watson F, Denham R, Khanal G. 2013. The use of multi temporal LiDAR
586 to assess basin-scale erosion and deposition following the catastrophic January 2011 Lockyer flood,
587 SE Queensland, Australia. *Geomorphology* 184:111-126.

588 Death RG. 2008. Effects of floods on aquatic invertebrate communities. Pages 103-121 in Lancaster J,
589 Briers RA, eds. *Aquatic Insects: Challenges to Populations*. UK: CAB International.

590 Death RG, Fuller IC, Macklin MG. 2015. Resetting the river template: the potential for climate-
591 related extreme floods to transform river geomorphology and ecology. *Freshwater Biology*:n/a-n/a.

592 Dollar ESJ, James CS, Rogers KH, Thoms MC. 2007. A framework for interdisciplinary understanding
593 of rivers as ecosystems. *Geomorphology* 89: 147-162.

594 Donat MG, Lowry AL, Alexander LV, O'Gorman PA, Maher N. 2017. Addendum: More extreme
595 precipitation in the world's dry and wet regions. *Nature Climate Change* 7: 154-158.

596 Downes BJ, Miller F, Barnett J, Glaister A, Ellemor H. 2013. How do we know about resilience? An
597 analysis of empirical research on resilience, and implications for interdisciplinary praxis.
598 *Environmental Research Letters* 8, 014041, 1-8.

599 Downs PW, Dusterhoff SR, Sears WA. 2013. Reach-scale channel sensitivity to multiple human
600 activities and natural events: Lower Santa Clara River, California, USA. *Geomorphology* 189:121-134.

601 Downs PW, Gregory KJ. 1993. The sensitivity of river channels in the landscape system. *Landscape*
602 *sensitivity*. New York: John Wiley & Sons:15-30.

603 Edwards P, Kollmann J, Gurnell A, Petts G, Tockner K, Ward J. 1999. A conceptual model of
604 vegetation dynamics on gravel bars of a large Alpine river. *Wetlands Ecology and Management*
605 7:141-153.

606 Elosegi A, Díez J, Mutz M. 2010. Effects of hydromorphological integrity on biodiversity and
607 functioning of river ecosystems. *Hydrobiologia* 657:199-215.

608 Elosegi A, Sabater S. 2013. Effects of hydromorphological impacts on river ecosystem functioning: a
609 review and suggestions for assessing ecological impacts. *Hydrobiologia* 712:129-143.

610 Florsheim JL, Mount JF, Chin A. 2008. Bank erosion as a desirable attribute of rivers. *BioScience*
611 58:519-529.

612 Fryirs KA. 2013. (Dis)Connectivity in catchment sediment cascades: a fresh look at the sediment
613 delivery problem. *Earth Surface Processes and Landforms* 38:30-46.

614 Fryirs KA, Brierley GJ, Erskine WD. 2012. Use of ergodic reasoning to reconstruct the historical range
615 of variability and evolutionary trajectory of rivers. *Earth Surface Processes and Landforms* 37:763-
616 773.

617 Fryirs KA, Lisenby P, Croke J. 2015. Morphological and historical resilience to catastrophic flooding:
618 The case of Lockyer Creek, SE Queensland, Australia. *Geomorphology* 241:55-71.

619 Fryirs KA. 2017. River sensitivity: a lost foundation concept in fluvial geomorphology. *Earth Surface*
620 *Processes and Landforms* 42: 55-70.

621 Fryirs KA, Brierley GJ. 2013. *Geomorphic analysis of river systems : an approach to reading the*
622 *landscape*. Wiley.

623 Fuller IC, Basher L, Macklin MG. 2016. Natural Hazards. In: Jellyman P, Davie TJA, Pearson CP,
624 Harding JS (Eds) *Advances in New Zealand Freshwater Science*, 415-443.

625 Fuller IC, Richardson JM, Basher L, Dykes RC, Vale SS. 2012. Responses to river management?
626 Geomorphic change over decadal and annual timescales in two gravel-bed rivers in New Zealand. In:
627 Molina D. (Ed.), *River Channels: Types, Dynamics and Changes*, Nova Science, New York, 137-163.

628 Fuller IC, Basher L. 2013. Riverbed digital elevation models as a tool for holistic river management:
629 Motueka River, Nelson, New Zealand. *River Research and Applications* 29:619-633.

630 Fuller IC. 2008. Geomorphic impacts of a 100-year flood: Kiwitea Stream, Manawatu catchment,
631 New Zealand. *Geomorphology* 98:84-95.

632 Fuller IC, Heerdegen RG. 2005. The February 2004 floods in the Manawatu, New Zealand:
633 hydrological significance and impact on channel morphology. *Journal of Hydrology (New Zealand)*
634 44:75.

- 635 Garcia X-F, Schnauder I, Pusch M. 2012. Complex hydromorphology of meanders can support
636 benthic invertebrate diversity in rivers. *Hydrobiologia* 685:49-68.
- 637 Gilvear DJ, Greenwood MT, Thoms MC, Wood PJ. 2016. *River Science: Research and Management*
638 *for the 21st Century*. John Wiley & Sons.
- 639 Gilvear DJ. 1999. Fluvial geomorphology and river engineering: future roles utilizing a fluvial
640 hydrosystems framework. *Geomorphology* 31:229-245.
- 641 Gilvear DJ, Black AR. 1999. Flood-induced embankment failures on the River Tay: implications of
642 climatically induced hydrological change in Scotland. *Hydrological Sciences Journal* 44:345-362.
- 643 Gilvear DJ, Davies JR, Winterbottom SJ. 1994. Mechanisms of floodbank failure during large flood
644 events on the rivers Tay and Earn, Scotland. *Quarterly Journal of Engineering Geology and*
645 *Hydrogeology* 27:319-332.
- 646 Gilvear DJ, Winterbottom SJ. 1992. Channel change and flood events since 1783 on the regulated
647 river tay, Scotland: Implications for flood hazard management. *Regulated Rivers: Research &*
648 *Management* 7:247-260.
- 649 Graf WL. 1979. Catastrophe theory as a model for change in fluvial systems.
- 650 Gregory KJ, Lewin J. 2014. *The Basics of Geomorphology: key concepts*. Sage.
- 651 Gunderson LH, Holling CS, Pritchard L, Peterson GD. 2002. Resilience of large-scale resource systems.
652 In: Gunderson LH, Pritchard L. (Eds.), *Resilience and the Behaviour of Large-Scale Systems*. Island
653 Press, Washington, DC, pp. 3–20.
- 654 Gurnell AM. 2014. Plants as river system engineers. *Earth Surface Processes and Landforms* 39:4-25.
- 655 Gurnell AM, Corenblit D, García de Jalón D, González del Tánago M, Grabowski RC, O'Hare MT,
656 Szweczyk M. 2016. A Conceptual Model of Vegetation–hydrogeomorphology Interactions Within
657 River Corridors. *River Research and Applications* 32:142-163.
- 658 Hack JT. 1975. Dynamic equilibrium and landscape evolution. *Theories of landform development*
659 1:87-102.
- 660 Harvey AM. 2002. Effective timescales of coupling within fluvial systems. *Geomorphology* 44:175-
661 201.
- 662 Harvey AM, Hitchcock DH, Hughes DJ. 1979. Event frequency and morphological adjustment of
663 fluvial systems in upland Britain. Pages 139-167 in Williams DDRaGP, ed. *Adjustments of the Fluvial*
664 *System*. Dubuque, Iowa:: Kendall Hunt.
- 665 Hauer C, Habersack H. 2009. Morphodynamics of a 1000-year flood in the Kamp River, Austria, and
666 impacts on floodplain morphology. *Earth Surface Processes and Landforms* 34:654-682.
- 667 Hill A. 1987. Ecosystem stability some recent perspectives. *Progress in Physical Geography* 11:315-
668 333.
- 669 Hodges KE. 2008. Defining the problem: terminology and progress in ecology. *Frontiers in Ecology*
670 *and the Environment* 6:35-42.
- 671 Hodgson D, McDonald JL, Hosken DJ. 2015. What do you mean, 'resilient'? *Trends in Ecology &*
672 *Evolution* 30:503-506.
- 673 ---. 2016. Resilience Is Complicated, but Comparable: A Reply to Yeung and Richardson. *Trends in*
674 *Ecology & Evolution* 31:3-4.
- 675 Hohensinner S, Jungwirth M, Muhar S, Schmutz S. 2014. Importance of multi-dimensional
676 morphodynamics for habitat evolution: Danube River 1715–2006. *Geomorphology* 215:3-19.

677 Holling CS. 1973. Resilience and Stability of Ecological Systems. *Annual Review of Ecology and*
678 *Systematics* 4:1-23.

679 Holling CS. 1996. Engineering resilience versus ecological resilience. *Engineering within ecological*
680 *constraints* 31:32.

681 Holling CS. 2001. Understanding the complexity of economic, ecological, and social systems.
682 *Ecosystems*, 4: 390-405.

683 Howard AD. 1982. Equilibrium and time scales in geomorphology: Application to sand-bed alluvial
684 streams. *Earth Surface Processes and Landforms* 7: 303-325.

685 Jackson JR, Pasternack GB, Wheaton JM. 2015. Virtual manipulation of topography to test potential
686 pool-riffle maintenance mechanisms. *Geomorphology* 228:617-627.

687 Kale VS, Pramod H, Baker VR. 1997. Flood hydrology and geomorphology of monsoon-dominated
688 rivers: The Indian peninsula. *Water International* 22.

689 Kasai M, Marutani T, Brierley G. 2004. Channel bed adjustments following major aggradation in a
690 steep headwater setting: findings from Oyabu Creek, Kyushu, Japan. *Geomorphology* 62:199-215.

691 Knight J, Harrison S. 2014. Limitations of uniformitarianism in the Anthropocene. *Anthropocene*
692 5:71-75.

693 Knox JC. 2000. Sensitivity of modern and Holocene floods to climate change. *Quaternary Science*
694 *Reviews* 19:439-457.

695 Lake P. 2000. Disturbance, patchiness, and diversity in streams. *Journal of the north american*
696 *Benthological society* 19:573-592.

697 Lessard J, Murray Hicks D, Snelder TH, Arscott DB, Larned ST, Booker D, Suren AM. 2013. Dam Design
698 can Impede Adaptive Management of Environmental Flows: A Case Study from the Opuha Dam, New
699 Zealand. *Environmental Management* 51:459-473.

700 Macklin MG, Lewin J, Woodward JC. 2012. The fluvial record of climate change. *Philosophical*
701 *Transactions of the Royal Society a-Mathematical Physical and Engineering Sciences* 370:2143-2172.

702 Meyer K. 2016. A MATHEMATICAL REVIEW OF RESILIENCE IN ECOLOGY. *Natural Resource*
703 *Modeling*:n/a-n/a.

704 Michalková M, Piégay H, Kondolf GM, Greco SE. 2011. Lateral erosion of the Sacramento River,
705 California (1942–1999), and responses of channel and floodplain lake to human influences. *Earth*
706 *Surface Processes and Landforms* 36:257-272.

707 Milan D, Heritage G, Large A, Entwistle N. 2010. Mapping hydraulic biotopes using terrestrial laser
708 scan data of water surface properties. *Earth Surface Processes and Landforms* 35:918-931.

709 Muhammad A, Muhammad T, Mehtab G, Mujtaba B, Iftikhar A, Usman A, Al-Tawabini BS. 2013.
710 Unusual rainfall shift during monsoon period of 2010 in Pakistan: flash flooding in northern Pakistan
711 and riverine flooding in southern Pakistan. *African Journal of Environmental Science and Technology*
712 7.

713 Newson MD, Large ARG. 2006. 'Natural' rivers, 'hydromorphological quality' and river restoration: a
714 challenging new agenda for applied fluvial geomorphology. *Earth Surface Processes and Landforms*
715 31:1606-1624.

716 Nimmo DG, Mac Nally R, Cunningham SC, Haslem A, Bennett AF. 2015. Vive la résistance: reviving
717 resistance for 21st century conservation. *Trends in Ecology & Evolution* 30:516-523.

718 Oldmeadow DF, Church M. 2006. A field experiment on streambed stabilization by gravel structures.
719 *Geomorphology* 78:335-350.

720 Page M, Marden M, Kasai M, Gomez B, Peacock D, Betts H, Parkner T, Marutani T, Trustrum N. 2007.
721 13 Changes in basin-scale sediment supply and transfer in a rapidly transformed New Zealand
722 landscape. Pages 337-356 in Helmut Habersack HP, Massimo R, eds. *Developments in Earth Surface*
723 *Processes*, vol. Volume 11 Elsevier.

724 Parsons M, Thoms MC, Flotemersch J, Reid M. 2016. Monitoring the resilience of rivers as social–
725 ecological systems: a paradigm shift for river assessment in the twenty-first century. *River Science:*
726 *Research and Management for the 21st Century*:197-220.

727 Phillips CB, Jerolmack DJ. 2016. Self-organization of river channels as a critical filter on climate
728 signals. *Science* 352:694-697.

729 Phillips JD. 2009. Changes, perturbations, and responses in geomorphic systems. *Progress in Physical*
730 *Geography* 33:17-30.

731 Phillips JD. 2011. Emergence and pseudo-equilibrium in geomorphology. *Geomorphology* 132:319-
732 326.

733 ---. 2014. Thresholds, mode switching, and emergent equilibrium in geomorphic systems. *Earth*
734 *Surface Processes and Landforms* 39:71-79.

735 Phillips JD, Van Dyke C. 2016. Principles of geomorphic disturbance and recovery in response to
736 storms. *Earth Surface Processes and Landforms* 41:971-979.

737 Piégay H, Chabot A, Le Lay Y-F. 2018. Some comments about resilience: From cyclicity to trajectory, a
738 shift in living and nonliving system theory. *Geomorphology* in press
739 <https://doi.org/10.1016/j.geomorph.2018.09.018>

740 Piégay H, Darby SE, Mosselman E, Surian N. 2005. A review of techniques available for delimiting the
741 erodible river corridor: a sustainable approach to managing bank erosion. *River Research and*
742 *Applications* 21:773-789.

743 Pimm SL. 1984. The complexity and stability of ecosystems. *Nature* 307:321-326.

744 Poff LN, Allan JA, Bain MB, Karr JR, Prestegard KL, Richter BD, Sparks RE, Stromberg JC. 1997. The
745 natural flow regime: a paradigm for river conservation and restoration. *BioScience* 47:769-784.

746 Poole GC. 2010. Stream hydrogeomorphology as a physical science basis for advances in stream
747 ecology. *Journal of the North American Benthological Society* 29:12-25.

748 Raven EK, Lane SN, Bracken LJ. 2010. Understanding sediment transfer and morphological change
749 for managing upland gravel-bed rivers. *Progress in Physical Geography* 34:23-45.

750 Reid H, Brierley G. 2015. Assessing geomorphic sensitivity in relation to river capacity for
751 adjustment. *Geomorphology* 251:108-121.

752 Rice S, Stoffel M, Turowski JM, Wolf A. 2012. Disturbance regimes at the interface of geomorphology
753 and ecology. *Earth Surface Processes and Landforms* 37:1678-1682.

754 Rinaldi M, Surian N, Comiti F, Bussettini M. 2013. A method for the assessment and analysis of the
755 hydromorphological condition of Italian streams: The Morphological Quality Index (MQI).
756 *Geomorphology* 180:96-108.

757 Rosgen DL. 1996. *Applied river morphology*. Wildland Hydrology.

758 Rykiel EJ. 1985. Towards a definition of ecological disturbance. *Australian Journal of Ecology* 10: 361-
759 365

760 Schumm SA. 1969. River metamorphosis. *Journal of the Hydraulics Division of the American Society*
761 *of Civil Engineers* 95: 255–273.

762 Schumm SA. 1979. Geomorphic Thresholds: The Concept and Its Applications. Transactions of the
763 Institute of British Geographers 4:485-515.

764 Schumm SA. 1998. To Interpret the Earth: Ten ways to be wrong. Cambridge University Press.

765 Schumm SA, Lichty RW. 1963. Channel widening and flood-plain construction along Cimarron River
766 in southwestern Kansas. Report no. 2330-7102.

767 Schumm SA, Lichty RW. 1965. Time, space, and causality in geomorphology. American Journal of
768 Science 263:110-119.

769 Statzner B, Fievet E, Champagne JY, Morel R, Herouin E. 2000. Crayfish as geomorphic agents and
770 ecosystem engineers: biological behavior affects sand and gravel erosion in experimental streams.
771 Limnology and Oceanography 45: 1030-1040.

772 Stanford JA, Lorang MS, Hauer FR. 2005. The shifting habitat mosaic of river ecosystems. Pages 123-
773 136 in Jones J, ed. International Association of Theoretical and Applied Limnology, Vol 29, Pt 1,
774 Proceedings, vol. 29.

775 Tereraï F, Gaertner M, Jacobs SM, Richardson DM. 2015. Resilience of invaded riparian landscapes:
776 the potential role of soil-stored seed banks. Environmental management 55: 86-99.

777 Thompson C, Croke J. 2013. Geomorphic effects, flood power, and channel competence of a
778 catastrophic flood in confined and unconfined reaches of the upper Lockyer valley, southeast
779 Queensland, Australia. Geomorphology 197:156-169.

780 Thompson C, Croke J, Takken I. 2008. A catchment-scale model of mountain stream channel
781 morphologies in southeast Australia. Geomorphology 95:119-144.

782 Thoms M, Walker K. 1992. Channel changes related to low-level weirs on the River Murray, South
783 Australia. Lowland floodplain rivers: Geomorphological perspectives:235-249.

784 Thoms MC, Piégay H, Parsons M. 2018. What do you mean, 'resilient geomorphic systems'?.
785 Geomorphology 305, 8-19.

786 Thorn CE, Welford MR. 1994. The Equilibrium Concept in Geomorphology. Annals of the Association
787 of American Geographers 84:666-696.

788 Thorp JH. 2008. The riverine ecosystem synthesis : toward conceptual cohesiveness in river science.
789 Academic Press.

790 Thorp JH, Thoms MC, Delong MD. 2006. The riverine ecosystem synthesis: Biocomplexity in river
791 networks across space and time. River Research and Applications 22:123-147.

792 Trimble SW, Mendel AC. 1995. The cow as a geomorphic agent—a critical review. In
793 Biogeomorphology, Terrestrial and Freshwater Systems, pp. 233-253.

794 Tunnicliffe J, Brierley GJ, Fuller IC, Leenman AS, Marden M, Peacock DH. 2018. Reaction and
795 relaxation in a coarse-grained fluvial system following catchment-wide disturbance. Geomorphology,
796 307, 50-64

797 Vannote RL, Minshall GW, Cummins KW, Sedell JR, Cushing CE. 1980. The river continuum concept.
798 Canadian Journal of Fisheries and Aquatic Sciences 37:130-137.

799 Walker B, Holling CS, Carpenter S, Kinzig A. 2004. Resilience, adaptability and transformability in
800 social–ecological systems. Ecology and society, 9.

801 Walker B, Salt D. 2006. Resilience thinking: sustaining ecosystems and people in a changing world
802 Island Press. Washington, DC.

803 Walker B, Salt D. 2012. Resilience thinking: sustaining ecosystems and people in a changing world.
804 Island Press.

805 Werritty A. 1997. Short-term changes in channel stability. In: Thorne CR, Hey RD, Newson MD (Eds.)
806 Applied Fluvial Geomorphology for River Engineering and Management, Wiley, Chichester, 47-65.

807 Westman WE. 1978. Measuring the inertia and resilience of ecosystems. *BioScience* 28:705-710.

808 Wittenberg L, Newson MD. 2005. Particle clusters in gravel-bed rivers: an experimental
809 morphological approach to bed material transport and stability concepts. *Earth Surface Processes*
810 *and Landforms* 30:1351-1368.

811

812 Wohl E. 2014. Time and the rivers flowing: Fluvial geomorphology since 1960. *Geomorphology*
813 216:263-282.

814 ---. 2016a. Spatial heterogeneity as a component of river geomorphic complexity. *Progress in*
815 *Physical Geography* 40:598-615.

816 ---. 2016b. Messy rivers are healthy rivers: The role of physical complexity in sustaining ecosystem
817 processes. *River Flow 2016: Iowa City, USA, July 11-14, 2016*, 24.

818 Yeung ACY, Richardson JS. 2016. Some Conceptual and Operational Considerations when Measuring
819 'Resilience': A Response to Hodgson et al. *Trends in Ecology & Evolution* 31:2-3.

820 Yuill BT, Gaweesh A, Allison MA, Meselhe EA. 2016. Morphodynamic evolution of a lower Mississippi
821 River channel bar after sand mining. *Earth Surface Processes and Landforms* 41:526-542.

822

823 **Table 1:** Key terms of resilience and geomorphology. Note: the terms are listed alphabetically and do not equate with one another. Key
824 references in text.

Resilience	Definition	Geomorphology	Definition
Adaptability	The capacity of actors in a system to influence resilience (Walker et al. 2004)	Catastrophe theory	A mathematical theory that models the mechanisms of sudden and discontinuous change of state in very different types of phenomenon like river ecosystems. (Graf 1979)
Basin of attraction	The set of points defining the space of system. A state has been described in resilience thinking as the ball and cup model. The cup part of the model is envisaged as a 'state space' or 'basin' while the ball part of the model is defined by the variables that constitute the system for the problem of interest. (Thoms et al. 2017)	Equilibrium	There are many different types of equilibrium referred to in geomorphic systems and these are: <i>Static</i> equilibrium: where a balance of tendencies results in a static condition – a state of no change; <i>Stable</i> equilibrium: the tendency for a system to move back towards a previous equilibrium condition ie., to recover after being disturbed by external forces;

Unstable equilibrium: where small displacement leads to a greater change and usually achievement of a new stable equilibrium;

Metastable equilibrium: when stable equilibrium obtains only in the absence of a suitable trigger which carries the system state over a threshold into a new equilibrium regime.

Steady state equilibrium: where system properties are invariant to a given time scale but may oscillate around a mean state because of the presence of interacting variables;

Dynamic equilibrium: balanced fluctuations about a constantly changing system condition may have a trajectory of unrepeated states which overtime.

(e.g. Thorn and Welford 1994)

Connectedness	The internal controllability of a system, or the degree of connectedness between internal controlling variables and processes; connectedness reflects the degree of flexibility and rigidity of controls and the sensitivity of the system to perturbation (Holling 2001)	Relaxation time	The time taken by a system to adjust to a change in energy input (e.g. Howard 1982; Thoms et al. 2018)
Latitude	Changes in the character of the cup (Thoms et al. 2017)	System	A set of interrelated parts and are defined as having three basic components; elements, states and relations between elements and states (Thoms et al. 2018)
Resilience	The capacity of a system to absorb disturbance and reorganize while undergoing change so as to still retain essentially the same function, structure, identity, and feedbacks (e.g. Walker et al. 2004)	Threshold	A threshold of landform stability can be exceeded either by intrinsic change of the landform itself or by change of an external variable. <i>An intrinsic</i> threshold implies changes can take place within a system without a change in an external variable. <i>An extrinsic</i> threshold describes change triggered by an external variable.

(Schumm 1979)

Resistance	The difficulty to change within a basin of attraction or how difficult it is to move the ball around the cup (Thoms et al. 2018)
------------	--

825

826

827

Case Study 1: River trajectories of change and resilience: River Murray, Australia

A range of trajectories can be illustrated in the response of reaches along part of an 830 km section of the River Murray below the Darling junction (the lower Murray), in SE Australia. This reach of the River Murray (Figure Case Study 1 a) receives no major tributary flow. Flows are controlled mainly by large upland reservoirs (Jacobs, 1990), but along the lower Murray there are 10 low-level weirs constructed in 1922-35. The presence of these weirs has initiated a series of river channel adjustments (Thoms and Walker 1992) showing three basic responses:

1) Stabilizing river morphology (Locks 3-4, 8-10). After an initial period of fluctuation the cross section attained a new dynamic equilibrium, 30-40 years after closure of the weir, where it is 100-200 percent larger than the pre-regulation value. As such the alteration amplitude has exceeded resilience and this provides an illustration of meta-stable resilience (Figure Case Study 1 b). It is interesting to note the response of these weirs to a major flood in 1976 (peak $1078 \text{ m}^3 \text{ s}^{-1}$). Cross sections below Locks 3 and 4 increased by 106 and 313 m^2 after the flood, but returned to pre-1976 values two years later. If these cross sections had not been in equilibrium with the regulated regime the pre-flood values may not have been returned to pre-flood values (as happened after a much larger flood in 1956). It is likely that the present cross-sectional areas will be maintained while the regulated regime persists.

2) Eroding river morphology (Locks 5-7). The first stage is similar to the stabilising response described above in that there is an initial period of fluctuation. Subsequently, erosion and enlargement of the channel have continued since the 1950s. As such the

850 reach is continuing to adjust, resistance exceeds recovery and resilience is dynamic
851 (Figure Case Study 1 b).

852 3) Fluctuating or instability of river morphology (Locks 1-2). This response is distinctive
853 because no clear pattern of adjustment is evident and the fluctuations appear to be
854 independent of variations in discharge. There is some synchrony in changes in the
855 cross-sectional area below Locks 1 and 2, and the magnitude of the changes is greatest
856 below Lock 1, the furthest downstream weir. Here resistance could be construed as
857 being equivalent to recovery, and resilience is in a steady-state (Figure Case Study 1 b,
858 NB x-axis shows years).

859

860

861 Figure Case Study 1 a. The Lower River Murray, South Australia. Flows in the River
862 Murray, below its confluence with the Darling River, is regulated a series of 10 lock and weir
863 systems.

864

Figure Case Study 1 b. Trajectories of river channel behaviour downstream of 10 weirs (Locks 1-10) along the lower River Murray. Bankfull cross section areas are given (see Thoms and Walker, 1993)

870 **Case Study 2:** River management and resilience on the River Tay, Scotland

871 Research on the River Tay in Scotland (Gilvear and Winterbottom 1992) using old maps has
872 shown how reach morphologies have been altered from moderately sinuous and active and
873 wandering gravel bed ones to less sinuous and active channels with agricultural
874 embankments on each side. During time periods lacking large floods the channel prevents
875 inundation of the floodplain and allows farming. Thus during the 1970s and 1980s, flood
876 events causing failures were in the order of one per decade. However, during large floods
877 causing overtopping, such as ones in 1990 and 1993, multiple embankment failures
878 occurred causing large scour holes and stripping of soil along the lines of relic channels
879 (Gilvear et al. 1994). Gilvear and Black (1999) demonstrated that an upward shift in flood
880 peaks of 5%, over the historical record dating back to the 1950s, could create an increase in
881 embankment failures of up to 25%. Since 2000 a “flood-rich” period consistent with climate
882 change predictions of flood magnitude and frequency have led to frequent flood
883 embankment failures (in the order of every 3 years). Subsequently, costly human
884 intervention is required to make the floodplain suitable for agriculture. The channel and
885 floodplain morphology, under the embanked conditions, had very low resilience to the
886 recent heightened flood peak regime and the current river management approach is
887 effectively unsustainable. In reaches lacking embankments adjacent to the channel, it is
888 noticeable how floods cause some minor channel morphological adjustment and inundate
889 the floodplain, but with very little geomorphic consequence, such reaches are far more
890 resilient to natural shifts in flood regime, and healthy river habitat is maintained. Since
891 instability in some form is the norm in naturally adjusting, absorbing, resisting, recovering
892 river systems, river management ought to take this into account (Newson and Large 2006).
893 Failure to do so alters sediment dynamics and results in loss of habitat heterogeneity

894 (Downs et al. 2013, Edwards et al. 1999). There is thus a need in many engineered rivers to
895 rehabilitate resilience, to allow for disturbance and recovery to disturbance, which is part of
896 natural reach behaviour particularly in this flood-rich era that seems to be apparent globally
897 (Thoms et al. 2018).

898

899 List of Figures

900 **Figure 1.** Bivariate composition of resilience defined. Resilience comprises both resistance to and
901 recovery from disturbance. For example, a bedrock river will have a high resistance to change usually
902 retaining its form regardless of the magnitude of a flood event. Highly engineered channels will also
903 be resistant to flows for which they have been designed. In contrast a braided system is readily
904 'disturbed' by small events that reshape channels and bars. However, braided rivers have a high
905 propensity for recovery from floods, retaining their form while not resisting change. When
906 engineered channels are altered by floods that exceed their design capacity, they have a low
907 recovery potential, similarly, a meandering channel that has been naturally straightened by cutoffs
908 during a large flood will have a lower recovery potential (i.e. take longer) to recover its original
909 sinuous form. What constitutes a resilient river is discussed later in this paper.

910 **Figure 2.** Resilience defined in a process-response system, which characterises geomorphic
911 processes in river geomorphology. Resilience comprises resistance and recovery. Disturbance may
912 produce no response (a), or a lagged response (b), or an immediate response (c), depending on the
913 geomorphic sensitivity of the system (Phillips and Van Dyke 2016). An example of a lower system
914 resilience threshold in the channel continuum concept might be straight (below the line) to
915 meandering (above the line).

916 **Figure 3.** Resilience trajectories (a) steady state, (b) dynamic, (c) static, (d) meta-stable

917 **Figure 4.** Resilience in amplitude, frequency and recovery space.

918 **Figure 5.** Aerial photo sequence of the lower Kiwitea Stream, near Feilding, New Zealand. A 100
919 yr flood in 2004 resulted in catastrophic widening of the river corridor, visible in the 2005
920 photography. Engineering has since modified the river corridor, but maintains sufficient width to
921 accommodate large floods without resulting in the same large-scale changes of 2004. The red
922 dashed line indicates the margin of the managed channel fairway. Image supplied courtesy of Peter
923 Blackwood, Horizons Regional Council. Insert shows an oblique view of the channel transformation

and destruction of the approach to a State Highway bridge, located just to the far right (downstream) of the photo sequence. Note: the bridge remained intact and the pre-flood channel is clearly visible underneath it.

Figure 6. Transformation of a river in Haiti in response to Hurricane Matthew, October 2016. Flow is from top to bottom of the image.

Figure 7. Change in resilience with changes to disturbance events. Scenarios represented on the left of the diagram are typical of pulse disturbance, while a ramp disturbance is evident in scenarios on the right. The scenario of change in resistance to disturbance shows reducing resistance with each event and associated increase in response to ramp disturbance.

Figure 1. Bivariate composition of resilience defined. Resilience comprises both resistance to and recovery from disturbance. For example, a bedrock river will have a high resistance to change usually retaining its form regardless of the magnitude of a flood event. Highly engineered (e.g. straightened) channels will also be resistant to flows for which they have been designed. In contrast a braided system is readily ‘disturbed’ by small events that reshape channels and bars. However, braided rivers have a high propensity for recovery from floods, retaining their form while not resisting change. When engineered channels are altered by floods that exceed their design capacity, they have a low recovery potential, similarly, a meandering channel that has been naturally straightened by cutoffs during a large flood will have a lower recovery potential (i.e. take longer) to recover its original sinuous form. What constitutes a resilient river is discussed later in this paper.

Figure 2. Resilience defined in a process-response system, which characterises geomorphic processes in river geomorphology. Resilience comprises resistance and recovery. Disturbance may produce no response (a), or a lagged response (b), or an immediate response (c), depending on the geomorphic sensitivity of the system (Phillips and Van Dyke 2016). Just as an example of a higher system resilience threshold is given between braided and meandering, so an example of a lower system resilience threshold in the channel continuum concept might be straight (below the line) to meandering (above the line).

952

953

954

Figure 3. Resilience trajectories (a) steady state, (b) dynamic, (c) static, (d) meta-stable

955

956

957

Figure 4. Resilience in amplitude, frequency and recovery space.

Figure 5. Aerial photo sequence of the lower Kiwitea Stream, near Feilding, New Zealand. A 100 yr flood in 2004 resulted in catastrophic widening of the river corridor, visible in the 2005 photography. Engineering has since modified the river corridor, but maintains sufficient width to accommodate large floods without resulting in the same large-scale changes of 2004. The red dashed line indicates the margin of the managed channel fairway. Image supplied courtesy of Peter Blackwood, Horizons Regional Council. Insert shows an oblique view of the channel transformation and destruction of the approach to a State Highway bridge, located just to the far right (downstream) of the photo sequence. Note: the bridge remained intact and the pre-flood channel is clearly visible underneath it.

Figure 6. Transformation of a river in Haiti in response to Hurricane Matthew, October 2016. Flow is from top to bottom of the image.

Figure 7. Change in resilience with changes to disturbance events. Scenarios represented on the left of the diagram are typical of pulse disturbance, while a ramp disturbance is evident in scenarios on the right. The scenario of change in resistance to disturbance shows reducing resistance with each event and associated increase in response to ramp disturbance.