2020-09

A global approach to mapping the environmental risk of commercial harbours on aquatic systems

Valdor, P

<http://hdl.handle.net/10026.1/15712>

10.1016/j.marpol.2020.104051

Marine Policy

Elsevier

All content in PEARL is protected by copyright law. Author manuscripts are made available in accordance with publisher policies. Please cite only the published version using the details provided on the item record or document. In the absence of an open licence (e.g. Creative Commons), permissions for further reuse of content should be sought from the publisher or author.

A global approach to mapping the environmental risk of commercial harbours on aquatic systems

Paloma F. Valdor^a, Aina G. Gómez^{a,m}, Peter Steinberg^{b,c}, Edwina Tanner^b, Antony M. Knights^d, Rochelle D. Seitz^e, Laura Airoidi^f, Louise B. Firth^d, Christos Arvanitidis^g, Massimo Ponti^f, Eva Chatzinikolaou^g, Paul R. Brooks^h, Tasman P. Crowe^h, , Alison Smith^e, Gonzalo Méndezⁱ, Aida Ovejeroⁱ, Abilio Soares-Gomes^j, John A. Burt^k, Catriona MacLeod^l, José A. Juanes^{a,*}

^a Environmental Hydraulics Institute, Universidad de Cantabria - Avda. Isabel Torres, 15, Parque Científico y Tecnológico de Cantabria, 39011, Santander, Spain, T:+34.942.20.16.16, palomavaldor@gmail.com, aina.gomez@unican.es, juanesj@unican.es

^b Sydney Institute of Marine Science, 19 Chowder Bay Rd, Mosman NSW 2088, Australia. p.steinberg@unsw.edu.au, Edwina.Tanner@sims.org.au

^c School of BEES, University of New South Wales Sydney, NSW 20152, Australia, p.steinberg@unsw.edu.au

^d School of Biological and Marine Sciences, University of Plymouth, Plymouth, U.K., louise.firth@plymouth.ac.uk, antony.knights@plymouth.ac.uk

^e Virginia Institute of Marine Science, William & Mary, Virginia, U.S.A., seitz@vims.edu, asmith@vims.edu

^f Department of Biological, Geological and Environmental Sciences and Interdepartmental Research Centre for Environmental Sciences, UO CoNISMa, University of Bologna, Via S. Alberto 163, 48123, Ravenna, Italy, laura.airoidi@unibo.it; massimo.ponti@unibo.it

^g Institute of Marine Biology, Biotechnology and Aquaculture Hellenic Centre for Marine Research, Attiki, Greece, arvanitidis@hcmr.gr, evachatz@hcmr.gr

^h UCD Earth Institute and School of Biology and Environmental Science, University College Dublin, Dublin, Ireland, paul.brooks@ucd.ie; tasman.crowe@ucd.ie

ⁱ UNESCO Chair in Sustainable Coastal Zone Management, University of Vigo, Vigo, Spain, mendez@uvigo.es, aovejero@uvigo.es

^j Sediment Ecology Laboratory, Marine Biology Department, Federal Fluminense University, Rio de Janeiro, Brazil, abiliosg@id.uff.br

^k Center for Genomics and Systems Biology, New York University Abu Dhabi, Abu Dhabi, United Arab Emirates, john.burt@nyu.edu

^l Institute for Marine and Antarctic Studies (IMAS), University of Tasmania, Australia, catriona.macleod@utas.edu.au

^m Balearic Islands Coastal Observing and Forecasting System (SOCIB), Parc Bit, Naorte, Bloc A 2º 3p, 07121 Palma de Mallorca, Spain

*Corresponding author E-mail addresses: juanesj@unican.es (José A. Juanes)

A global approach to mapping the environmental risk of harbours on aquatic systems

Highlights:

- A method is proposed to assess the environmental risk of commercial harbours on aquatic systems.
- The method is a tool to identify the factors of risk on harbour aquatic systems
- Results obtained from 15 globally distributed harbours are analysed
- Towards the creation of a global atlas of environmental risk of harbours on aquatic systems

Graphical abstract:

Abstract:

The goal of this paper is to propose a screening method for assessing the environmental risk to aquatic systems in harbours worldwide. A semi-quantitative method is based on environmental pressures, environmental conditions and societal response. The method is flexible enough to be applied to 15 harbours globally distributed through a multinational test using standardised and homogenised open data that can be obtained for any port worldwide. The method emerges as a useful approach towards the foundation of a global

19 environmental risk atlas of harbours that should guide the harbour sector to develop a
20 more globally informed strategy of sustainable development.
21 **Keywords:** environmental risk assessment; global atlas; pressure-state-response model;
22 harbour aquatic systems; harbour management; sustainable development.

24 1. INTRODUCTION

25 Shipping has an important role in moving about 90% of global trade, which is vital for the
26 continuing and sustainable development of the world economy (ICS, 2018; 2019). The
27 shipping sector is projected to continue to expand in the future with an estimated annual
28 growth rate of 3.2% by 2017-2022 (UNCTAD, 2017). The relevance of this sector for world
29 trade has placed this industry at the centre of a policy debate on globalisation, trade,
30 development and environmental sustainability (UNCTAD, 2012). Harbours are continuing to
31 expand to accommodate the infrastructure required to support growth in the shipping
32 industry (UNCTAD, 2012). This growth increases the likelihood of environmental damage,
33 which, to some extent, is being mitigated by harbour authorities embracing a sustainable
34 development approach (EC, 2013). Shipping, alongside the many other marine activities,
35 generates several threats of varying severity to marine ecosystems (Gómez et al., 2014;
36 Knights et al., 2015; Valdor et al., 2017), and harbours themselves can be some of the most
37 impacted habitats on Earth (Halpern et al., 2008).

39 The environmental sustainability of harbours needs to be focused on preventing the
40 impoverishment of aquatic systems caused by pollution from commercial ships or other
41 navigation activity. Harbours are guided and regulated by international legislation that aims
42 to limit ecosystem exposure to harmful activities. International bodies, like the International
43 Maritime Organisation (IMO), continue to develop legal frameworks to mitigate
44 environmental harm as a result of commercial shipping (e.g. IMO, 2004; 2013; 2014 or
45 Lethbridge, 1991), and they set the appropriate standards through international treaties and
46 conventions. Others, such as the World Association for Waterborne and Transport

47 Infrastructure (PIANC), provide expert guidance (PIANC, 2019), recommendations (PIANC,
48 2011) and technical advice (PIANC, 2020) on environmental issues related to both
49 recreational and commercial navigation activity (Brolsma, 2010). The maintenance of high-
50 quality aquatic systems (e.g. by preventing marine pollution) is a permanent and universal
51 goal of these conventions, guidelines and the research developed by these international
52 organisations. Consequently, water quality has been one of the top 10 environmental
53 priorities of the harbour sector over last years (2003-2009) (ESPO-ECOPORTS, 2019).

54
55 Scientific research that provides an evidence-based for decision-making related to
56 environmental risk on harbour aquatic systems is conducted by projects like the World
57 Harbour Project (WHP) (www.worldharbourproject.org, Steinberg et al., 2016). This project
58 enhances research and management across major urban harbours. To develop resilient
59 urban harbours, a global network of collaborating scientists works on different topics such
60 as ecological engineering (Strain et al., 2019), environmental management (Valdor et al.,
61 2019), accessible syntheses and summaries of current knowledge (e.g. Juanes et al.,
62 2020). Thus, research programs should be responsible in developing science and
63 communicating findings in an accessible way to a wide range of users to facilitate the
64 design of global strategies. We suggest that global strategies are needed to ensure that
65 harbour managers worldwide are able to assess the environmental risk on aquatic
66 systems using an easy-to-apply and versatile method. In this context, one of the main
67 objectives of global strategies is to provide standardised methods to analyse risk. In this
68 way, data among different harbours are comparable, and their management can be
69 adjusted to the best available practices regarding limiting environmental risk.

70
71 However, when global strategies are designed, the harbours' histories, the
72 geomorphological and environmental contexts and the socio-economic settings are very
73 different across the world (Steinberg et al., 2016) and thus may affect approaches to
74 environmental management. In that context, the Environmental Risk Assessment (ERA)

178
179
180 75 arises as a general management tool that is used worldwide to assess potential effects on
181
182 76 the environment due to the exposure to disturbing agents derived from different human
183
184 77 activities (e.g. fishery, industry, urban, agricultural or harbour activities, among others)
185
186 78 (AENOR, 2008; Hope, 2006; Smith et al., 2007; Samhouri and Levin, 2012; Valdor et al.,
187
188 79 2016). Using the ERA approach, the potential effects of environmental hazards on the
189
190 80 quality of aquatic systems in harbour areas have been widely studied (e.g. Ronza et al.,
191
192 81 2006; Grifoll et al., 2010; Gómez et al., 2015; Ondiviela et al., 2012; Parra et al., 2018), and
193
194 82 methods to assess the environmental risks of harbour activities have been proposed (e.g.
195
196 83 Gómez et al., 2015; Juanes et al., 2013; Ondiviela et al., 2012; Puig et al., 2015; Valdor et
197
198 84 al., 2016). However, worldwide studies to assess the environmental risk of harbour activities
199
200 85 on aquatic systems to support global strategies, such as Global Sustainable Development
201
202 86 Goals (United Nations, 2015), have not been conducted.

203
204 87 Harbours around the world implement different environmental management methods that
205
206 88 make use of different approaches to the characterisation of systems, use different analytical
207
208 89 tools and databases, thus making it challenging to obtain standardised quantitative data
209
210 90 globally (PIANC, 2019). For this reason, qualitative and semi-quantitative data analyses are
211
212 91 more suitable alternatives when conducting an ERA study at a global scale (Gómez et al.,
213
214 92 2019). Moreover, parameters, indicators, and assessment criteria should be carefully
215
216 93 selected to integrate the singularities of each specific harbour (Darbra et al., 2005; Gupta et
217
218 94 al., 2005). We suggest that, at the same time, the simplicity and low computing cost of the
219
220 95 method should allow for wider applicability to harbours of different sizes, hydrodynamic
221
222 96 characteristics, harbour uses and pressures or resources to assess environmental
223
224 97 challenges.

225 98
226
227 99 The goal of this paper is to propose a method for mapping the assessment of the
228
229 100 environmental risk of harbours on aquatic systems. This method will be: i) flexible enough
230
231 101 to be applied to any harbour worldwide; ii) open-data dependent; and iii) implemented to lay
232
233 102 the foundation to create a global atlas of environmental risk on aquatic systems of harbours.
234
235
236

237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295

103 The proposed method is tested by applying it to 15 harbours spread across five continents
104 worldwide. The main contributions of this study are: (i) the development of a standard and
105 unified ERA method to assess environmental risk of harbour activities worldwide on aquatic
106 systems (Section 2); (ii) the implementation of the ERA method in 15 harbours around the
107 world (Section 3); and (iii) the discussion of the proposed method and the results obtained
108 in the implementation (Section 4).

109 **2. MATERIALS AND METHODS**

110 The semi-quantitative method providing an assessment of environmental risk on aquatic
111 systems is based on the Pressure-State-Response (PSR) model defined by Gómez et al.
112 (2019) for marinas. The method comprises the following three steps: i) identification of
113 harbours and data collection; ii) estimation of the risk factors (environmental pressures of
114 harbour activities on the aquatic system, environmental conditions and management
115 responses); and iii) assessment of environmental risk.

116 **2.1 Identification of harbours**

117 Harbours are classified based on the typologies defined by the US National Geospatial-
118 Intelligence Agency (2015) into: i) coastal natural harbours are harbours that are sheltered
119 from the wind and sea due to their location within a natural coastline or occur in the protective
120 lee of an island, cape, reef or other natural barrier, or harbours that are located along a river;
121 ii) coastal breakwater harbours are harbours located behind a human-made breakwater that
122 are constructed to provide shelter or supplement inadequate shelter already provided by
123 natural resources; and iii) natural river harbours are harbours in which slips for vessels have
124 been excavated in the banks obliquely or at right angles to the axis of the stream.

125 For this study, general data, hydro-morphological characteristics and environmental
126 management information was gathered globally at all 15 harbours through a standardised
127 form (Supplementary Data. Appendix A) and through other sources of information (e.g.,
128 official harbour webpages).

2.2 Estimation of environmental risk

Environmental risk assessment at the harbour level was based on three factors: i) Pressures from human activities exerted on the environment; ii) State, or the environmental conditions that relate to the quality of the environment; and, iii) Response, or the extent to which the harbour responds to environmental concerns (OECD, 2003) (Eq.1).

Accordingly and based on Gómez et al., (2019), environmental risk of harbours on aquatic systems was estimated through the following formulas:

$$R_i = P_{ti} \times S_{ti} + R_{si} \quad (\text{Eq. 1})$$

$$R_i = (NV_i + HS_i + HO_i + CD_i) \times (SU_i + EV_i + NA_i) + (AM_i + AI_i) \quad (\text{Eq. 2})$$

Where R is the environmental risk, P_t is the Pressure, S_t is the State and R_s is the Response of an i harbour. Pressure is estimated considering the navigation activity (NV), the harbour services (HS), the harbour operation (HO) and the coastal development around the harbour (CD). While, State is estimated by combining the susceptibility (SU), the ecological value (EV) and the naturalness (NA). Finally, Response was estimated through the adopted measures (AM) and the Adopted Instruments (AI).

Estimation of environmental risk was evaluated using a semi-quantitative assessment criteria that was based on a combination of specific indicators, representative of a number of selected parameters for each factor (Table 1).

Table 1. Parameters, indicators, metrics and criteria assessment to estimate each environmental risk factor. (i: a specific harbour; max: maximum value obtained for a parameter considering all harbours under study; ISO: International Organisation for Standardisation; EMAS: Eco-Management and Audit Scheme; PERS: Port Environmental Review System). Unless specifically indicated by appropriate references to the source paper indicators were originally developed here.

Factor	Parameter	Indicator and metric (units)	Criteria assessment
Pressures	Navigation Activity (NV)	Density of trade vessels (vessels per year/m ²) by dividing vessels per year by the surface water area where the harbour activities take place.	$NV_i/NV_{\max}$ [0-1]

	Harbour Services (HS)	Harbour services: presence (1) or absence (0) of fuel oil and diesel oil supplies, major repair services and dangerous/hazardous goods handling within the area where the harbour activities take place (Valdor et al., 2016).	HS _i /HS _{max} [0-1]	
	Harbour Operation (HO)	Dredging probability, frequency of dredging operations.	Continual Periodic None	1.0 0.5 0.0
	Coastal Development (CD)	Land uses developed in a 1-km buffer distance around the harbour (worst case scenario) (Gómez et al., 2019).	Artificial Agricultural Natural - Other uses	1.0 0.5 0.0
State	Susceptibility (SU)	Flushing capacity of the water volume where harbour activities take place, combining hydrodynamic and morphological characteristics through the Complexity Tidal Range Index (CTRI*) (Gómez et al., 2017).	CTRI _i */CTRI _{max} * [0-1]	
	Ecological Value (EV)	Number of Protected areas (#) in a 1-km buffer distance around the surface water area where the harbour activities take place (Gómez et al., 2019).	EV _i /EV _{max} [0-1]	
	Naturalness (NA)	Alteration by hydro-morphological pressures in a harbour's environment (harbour's typology) (US National Geospatial-Intelligence Agency, 2015)	Open Roadstead Natural (Coastal or River) Coastal Breakwater/River Basin Tide Gates (Coastal or River)/Canal or Lake	1.0 0.75 0.5 0.0
Response	Adopted Measures (AM)	Number of adopted measures (#) to reduce the pressure of human activities on the environment (garbage disposal, dirty ballast management, etc.) (Gómez et al., 2019).	AM _i /AM _{max} [0-1]	
	Adopted Instruments (AI)	Number of adopted standards (#) to improve the environmental performance (ISO 14001, EMAS, PERS, others.) (Gómez et al., 2019).	AI _i /AI _{max} [0-1]	

$$*CTRI_i = \left[1 - \frac{4 \times A}{\pi \times L^2} \right] \times \frac{e}{R}$$
 Where A is the surface water area where the harbour activities take place (m²), L is the diameter of the smallest circle enclosing the surface water area polygon (m), e is the minimum distance between the harbour's infrastructures or the natural elements that conform the harbour's entry (m) and R is the medium tidal range (m) (Gómez et al., 2017).

The range of the potential values of all parameters were normalised (varying from 0 to 1) by dividing the observed value by the maximum value, after discarding outliers for each parameter with values greater than $\bar{x} \pm 3 \cdot SD$ (Gómez et al., 2019).

2.3. Environmental Risk Assessment

To assess the environmental risk to the harbour's aquatic systems, the results of pressure and state factors were classified into four categories (1 to 4), while the response factor was categorised by assigning one of either values: 0 or 4 (Table 2, Eq. 2). Levels separating the different categories were established for all harbours under study using the 25th, 50th and 75th percentile values, with the 50th percentile value used as the threshold between optimal and insufficient response (Table 2).

Table 2. Criteria to assess Pressures (Pr_i), State (St_i) and Response (R_{si}) categories from study site results (VL: Very low; L: low; M: moderate; H: high; P25: 25th Percentile; P50: 50th Percentile; P75: 75th Percentile).

Factor	Category	Criteria	Thresholds
Pressures (Pr)	VL (1)	$Pr_i \leq P_{25}$	$Pr_i \leq 2.11$
	L (2)	$P_{25} < Pr_i \leq P_{50}$	$2.11 < Pr_i \leq 2.51$
	M (3)	$P_{50} < Pr_i \leq P_{75}$	$2.51 < Pr_i \leq 2.58$
	H (4)	$Pr_i > P_{75}$	$Pr_i > 2.58$
State (St)	VL (1)	$St_i \leq P_{25}$	$St_i \leq 0.95$
	L (2)	$P_{25} < St_i \leq P_{50}$	$0.95 < St_i \leq 1.10$
	M (3)	$P_{50} < St_i \leq P_{75}$	$1.10 < St_i \leq 1.37$
	H (4)	$St_i > P_{75}$	$St_i > 1.37$
Response (Rs)	Optimal (0)	$R_{si} \geq P_{50}$	$R_{si} \geq 0.75$
	Insufficient (4)	$R_{si} < P_{50}$	$R_{si} < 0.75$

Obtained scores at the factor level (Table 2) were used to estimate the environmental risk of each harbour through Eq. 1. Based on the environmental risk value (Eq. 1), each harbour

was classified considering three categories: (i) high-risk harbour ($R_i \geq 12$), (ii) moderate-risk harbour ($6 \leq R_i < 12$), (iii) low-risk harbour ($1 \leq R_i < 6$).

3. RESULTS

3.1. Identification of harbours

The twenty-seven partners of World Harbour Project network were invited to participate to test the developed ERA method (Steinberg et al., 2016). Fifteen WHP partners were able to encourage harbour managers from their respective cities to participate and to gather the needed information. WHP partners contacted harbour managers by email or phone, and meetings were conducted when necessary. The fifteen harbours, where the developed ERA method was tested, spanned Europe (Dublin, Heraklion, Plymouth, Santander, Ravenna and Vigo), Australasia (Ashdod, Auckland, Darwin, Hobart, Hong Kong, Qingdao and Sydney) and the Americas (Baltimore and Rio de Janeiro) (Figure 1). “Coastal natural harbour” was the typology best represented by seven harbours (Rio de Janeiro, Qingdao, Hong Kong, Santander, Vigo, Darwin and Sydney), followed by “coastal breakwater harbours” represented by four harbours (Ashdod, Dublin, Heraklion, and Ravenna) and “natural river harbours” represented by four harbours (Baltimore, Plymouth, Auckland and Hobart) (Figure 1).

Figure 1. Harbours assessed using the ERA method.

195 The standardised form (Appendix A) was used to gather information from harbour
196 managers. Harbour managers sent the filled-in form through email to their respective local
197 WHP partner. In addition to consulting with harbour managers, where possible, data
198 collected was cross-checked using global, national (e.g. puertos.es) and local resources or
199 was specifically sourced from each harbour (e.g. the official web page of each harbour).
200 Using these sources of information, a database of metrics was generated for each harbour.

201 **3.2. Estimation of environmental risk**

202 The environmental risk assessment process provided explicit information on the parameters
203 of risk. To define the spatial scope, a polygon of the surface area of the water where harbour
204 activities take place was first digitalized using ArcGIS software. Harbour managers were
205 asked to approve the delimitation of these areas. The resulting polygons indicated harbour
206 surface-water areas (Supplementary data. Appendix B). The tools “extract by mask” and
207 “Clip” from the ArcGIS software were used to recognize both land uses and protected areas
208 in 1-km buffer around each harbour, using Globe Land 30 (Chen et al., 2015) and World
209 Database on Protected Areas (UNEP-WCMC, 2016), respectively. Mean tidal range (R, m),
210 as a hydrodynamic characteristic, was calculated from the GOS dataset (Cid et al., 2014);
211 morphological characteristics were estimated for each harbour using ArcGIS techniques,
212 including area (A, m²), applying the “calculate geometry” tool; length (L, m) and entrance
213 width (e, m), using the “minimum bounding geometry” tool (Gómez et al., 2017).

214 *Pressures:* Normalised values of navigation activity (NV) were extremely variable among the
215 studied harbours. Ashdod had the highest density of trade vessels (1), followed by Ravenna
216 (0.18), Dublin (0.16), Qingdao (0.15) and Rio de Janeiro (0.11), while the other harbours
217 showed normalised values lower than 0.07 (Figure 2, NV). Most harbour areas showed the
218 maximum value of Harbour Services (HS), since 10 of the 15 study sites develop fuel oil and
219 diesel oil supplies, major repair services and dangerous or hazardous goods handling
220 activities (Figure 2, HS). Exceptions to this were Hobart and Plymouth, where fuel oil supply

591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649

221 and major repairs are not developed, and Heraklion and Ravenna, where dangerous or
222 hazardous goods handling is not carried out. Harbour Operation (HO) was estimated
223 through dredging activities, which is are periodic operation in most of the harbours (0.5)
224 apart from Ashdod and Hong Kong, where continual dredging operations are undertaken
225 (1), and Hobart and Qingdao, where dredging operations are not carried out (Figure 2, HO).
226 Normalised Coastal development scored 1 in nearly all the harbours, since the land use
227 around the harbours was mainly artificial (urban, mining or industrial). Only one harbour
228 (Darwin) presented natural land uses in its surroundings (Figure 2, CD).

229
230 Figure 2. Representation of normalised values of the parameters applied for the estimation of the
231 environmental pressures (Pressures) at each of the 15 studied harbours

232
233 *State*: Susceptibility (SU, a measure of flushing capacity) was the most variable parameter
234 of State in all the 15 harbours studied (Figure 3, SU) as it is related to the cleaning capacity
235 of the water volume, which combines hydrodynamic and morphological characteristics at
236 the harbour level. The main characteristics of the harbours that were responsible for this
237 variability were the differences in water surface area ($\sim 0.8 \text{ km}^2$ in Plymouth, to 36.73 km^2 in

650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708

238 Darwin), the minimum distance between the elements that conform the harbour's entry (~0.2
239 km in Ravenna to ~316 km in Darwin) and the variability in tidal ranges (microtidal in the
240 Mediterranean to a 5 m tidal range in Plymouth). Regarding the Ecological Value (EV), the
241 number of protected areas located in a 1-km buffer distance around the harbour's water
242 surface area varied among the different harbours: 0 (five harbours), 1 (four harbours), 2 (two
243 harbours), 4 (two harbours) and 6 (two harbours) (Figure 3, EV). Conversely, naturalness
244 (NA) showed similar values at all harbours, with most of them (11) with a normalised NA
245 value of 0.75 and only 4 harbours with 0.5 (Figure 3, NA).

246
247 Figure 3. Representation of normalised values of the parameters applied for the estimation of
248 environmental conditions (State) at each of the 15 studied harbours.
249
250 Response: All studied harbours implemented a minimum of 3 Adopted Measures (AM) to
251 reduce the pressures of human activities on the environment (AM normalised value ≤ 0.5),
252 with 8 being the maximum number of measures applied in Qingdao and Baltimore (1 AM
253 normalised value) (Figure 4, AM). A higher variability was registered in the number of
254 Adopted Instruments (AI), with eight harbours where no instruments to achieve international

Figure 4. Representation of normalised values of the parameters applied for the estimation of level of response (Response), at each of the 15 studied harbours.

3.3. Environmental risk assessment

In terms of Pressure categories, two harbours were assessed to have high environmental pressure with four harbours assessed as being moderate. This was followed by a total of six harbours that were assessed as having low environmental pressures and, finally, three harbours with very low associated pressures (Figure 5, Pressures in blue bars). Regarding the State factor, four harbours were classified within the high category, with three harbours showing moderate environmental conditions and a total of eight harbours within the low and very-low categories (Figure 5, State in yellow bars). Finally, 7 of the 15 studied harbours showed insufficient environmental management, while 8 harbours presented an optimal level of management Response (Figure 5, Response in green bars).

Figure 5. Graphical representation of categorised risk factors (Pressures, State and Response) and categorised environmental risk to aquatic systems at each of the 15 studied harbours.

Results of environmental risk to aquatic systems of harbours, based on this study's results are shown in Supplementary data Appendix B.

4. DISCUSSION

4.1 Why this ERA method?: The conceptual model

From a conceptual point of view, the Pressure-State-Response (PSR) model (OECD, 2003) is used as a framework to select indicators that assess environmental risk at the harbour level, based on Gómez et al., (2019). Moreover, the Driving force-Pressure-State-Impact-Response (DPSIR) model (EEA, 2005) is integrated in the PSR model to define specific indices of Pressure, State and Response. These indices group and classify a small number of indicators (Figure 6).

827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885

289 From a practical point of view, the selection of general-purpose indicators for global
290 assessments was complex because of the need to obtain homogeneous, objective and
291 systematic, open and publicly available data and information on a series of diverse
292 parameters from analogous entities (harbours) that are under different socio-ecological
293 contexts from all over the world. Indicators were selected based on: i) the complementarity
294 and non-redundancy of indicators in their representation of risk factors; ii) the possibility of
295 finding available and homogeneous data from harbours worldwide, and iii) state-of-the-art
296 and previous studies.

297

298 Driving forces describe the social, demographic and economic development within a given
299 harbour (EEA, 2005). Based on the conceptual model presented (Figure 6), indicators
300 selected to estimate the environmental pressures include the four main driving forces
301 relevant to the harbour areas (navigation, harbour services, harbour operation and coastal
302 development). Navigation activity, estimated as the number of trade vessel visits per year
303 by a water-surface area of a harbour, was selected, as it has been identified in previous
304 works as a representative environmental stressor (Antão et al., 2016) and it is easily
305 accessible from institutional statistics (e.g. Eurostat, or individual webpages of harbours).
306 Regarding Harbours Services (HS), two indicators were selected: i) major repair services
307 (shipyards, ship repair or painting, etc.) that generate chemical wastes (heavy metals, PAHs
308 and antifoulants), which can pose a risk to aquatic organisms inhabiting harbour areas
309 (Bebianno et al., 2015); and ii) dangerous/hazardous goods handling defined by IMO codes
310 (IMO, 2014), which were previously considered in ERA mapping studies on harbour systems
311 (e.g. Valdor et al., 2016). Furthermore, dredging, one of the most important operations and
312 maintenance activities within harbours (PIANC, 2006), and dominant land use in the
313 surrounding area, served as proxies of the external influences on water quality (Cornelissen
314 et al., 2008).

315

886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944

316 Indirect or direct pressures are identified by each driving force (Gómez et al., 2019). The
317 identified pressures produce impacts altering the state of the environment (Ondiviela et al.,
318 2013; Petrosillo et al., 2010). State factor of risk considers three important aspects of the
319 harbour's environment: susceptibility, ecological value and naturalness. From the eight
320 pressure indicators proposed in the conceptual model (Figure 6), there are three related to
321 quality of the aquatic system (chemical quality, physico-chemical quality and biological
322 quality) that require periodic monitoring and systematic evaluation. Since each country
323 applies different monitoring and evaluation systems (in terms of thresholds, frequency, etc.),
324 the susceptibility to water and sediment contamination was considered as a standard
325 representative indicator of the quality of the aquatic system of harbours worldwide, assuming
326 a significant relationship between flushing capacity and water quality in littoral areas
327 (Ferreira et al., 2005; Fortes and Silva., 2006; Gómez et al, 2014; Yin et al., 2000). This
328 assumption was previously used for ERA in marinas (Gómez et al., 2017) and harbours
329 (Gómez et al., 2015). The harbour's ecological value considered that the greater the
330 protected area in the vicinity of the harbours is, the greater the biodiversity and ecological
331 processes that maintain that system (Gómez et al., 2015; Langanke et al., 2005; Margulles
332 and Usger, 1981). Finally, their 'naturalness' (Machado, 2004) was estimated using the
333 harbour typology (US National Geospatial-Intelligence Agency, 2015) as a surrogate of
334 number and dimensions of hydro-morphological pressures at the marina level typology
335 (Gamito, 2008; Gómez et al., 2019).

336

337 The response factor to environmental risk was used to integrate the actions and reactions,
338 intended to mitigate, adapt to or prevent human-induced negative effects on the environment
339 that could be applied to minimize the impacts of driving forces and improve the state of
340 aquatic ecosystems (OECD, 2003). Responses may arise from different sectors, such as
341 those in social, technical or institutional (i.e. local, national or international administrations)
342 realms (Figure 6). Among all of them, institutional responses are the option that integrates
343 a greater number of fields involving social responses (awareness campaigns), institutional

Figure 6. Conceptualisation of the causal links between main driving forces, pressures, impacts, state and response of aquatic systems in harbours.

4.2 The global implementation

Based on this study's results, the method used provides a tool to standardize the assessment of environmental risk to aquatic systems at a global scale (Supplementary data Appendix B). However, a question arose from this implementation: Are the PSR and DPSIR scenarios of the study sites representative of the environmental risks of harbours globally? ERA results showed that most of the study areas had a moderate risk but included significant variability of environmental pressures, environmental conditions and societal responses. However, results showed differences at the indicator level in those harbours within the same

1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062

361 category of risk. For instance, Hobart showed a moderate environmental risk on the aquatic
362 system due to a combination of high vulnerability (high naturalness but a moderate
363 ecological value of the surroundings) with a high score of environmental management (due
364 to the low number of adopted measures and none of the international standards
365 implemented). Heraklion showed a moderate risk on the aquatic system even though they
366 were adopting a good number of environmental measures (above the average) to reduce
367 the pressure of human activities on the environment because no international environmental
368 management instruments were applied. In other cases, the higher susceptibility (Baltimore)
369 or the higher ecological value (Ravenna), were the parameters of risk that penalised the
370 result for these harbours. Identification of such risk parameters allows for the targeted
371 application of more preventive and corrective management actions to help reduce
372 environmental risk to aquatic systems for those specific harbours.
373 Therefore, from a practical perspective, the environmental risk assessment method can be
374 used as a tool to proactively identify the most important factors of risk on which to apply
375 actions that allow for environmental improvements in each.
376 For this, expert knowledge on environmental risk is not strictly necessary, but a deep
377 understanding on the environment harbour characteristics is needed. These data are
378 controlled and known by harbour managers. In Section 2, practical steps are described
379 considering parameters, indicators, metrics and criteria to estimate each risk factor. The
380 pathway to apply the ERA method to an individual harbour include the collection of the
381 information needed and the calculation of parameters for each risk factor. A standardized
382 form to gather the information is provided in Appendix A and calculations described at
383 Section 2 are easy to apply with a basic knowledge of spatial analysis using geographical
384 information systems.
385 Once applied, the method can be used to detect which harbours should apply environmental
386 measures or/and international standards to improve their management of aquatic systems,
387 based on the highest standards of environmental quality applied around the world. An
388 example of this is shown in Figure 7, which represents the hypothetical case in which the 15

Figure 7. Graphical representation of a hypothetical situation at each of the 15 studied harbours with reduced categorised risk factors (pressures, state and responses) by the application of at least 4 environmental measures and 1 international standard and categorised environmental risk to aquatic systems.

In this case, one harbour continues to show high risk, five harbours show moderate risk while the other nine show a low environmental risk on the aquatic system. The screening capacity of this tool may address the global challenge of standardizing methods that produce comparable risk assessments of high-level entities (e.g. harbours) at large spatial scales. However, if the harbours applying the environmental measures and certifications do not obtain a low value of environmental risk, they should then focus their efforts on reducing the

1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180

406 environmental risk factors that are penalizing the final value of environmental risk. This is
407 the case in Hong Kong, which has high pressures due to the presence of intense navigation
408 activity (NV), the harbour services (HS) provided in the harbour, the continual dredging
409 activity (DG) in the harbour area and the Coastal development (CD) in their surroundings.
410 Baltimore is also highly susceptible probably due to the morphological characteristics of the
411 harbour area, which is very difficult to change from an environmental management
412 standpoint. In these cases, socio-economic issues should also be incorporated into a long-
413 term sustainability or management plan, which must assess the disadvantages and benefits
414 that may result from modifying factors that penalized the final value of the environmental
415 risk.

416

417 To the extent that harbours collaborate by providing the necessary information for the
418 calculation of environmental risk, it will be possible to create a global atlas of risk.
419 Collaboration by harbours will be feasible as long as the global atlas were understood as a
420 participatory process towards the sustainability of aquatic systems, recalling the adoption of
421 the 2030 Agenda and its Sustainable Development Goals (SDG, in particular SDG 14) and
422 the more recent resolution of the UN on the Decade for Ocean Sciences (2021-30), which
423 will provide a unifying framework across the UN system to enable countries to achieve all of
424 their ocean-related Agenda 2030 priorities (IOC, 2017).

425

426 The global atlas developed by using the method presented herein would introduce valuable
427 ~~bring the~~ elements of judgment to guide managers involved in decision-making (AENOR,
428 2008) towards the sustainability of aquatic systems in harbour areas, as well as to design
429 the first global strategy for sustainability related to the water quality at a global level.
430 Sustainable development goal (SDG) 14 in the UN 2030 Agenda requires to “conserve and
431 sustainably use the oceans, seas and marine resources for sustainable development”
432 (United Nations, 2015). Global Sustainable development goals require global analysis of the
433 problems presented and definition of global strategies to resolve them. Many critical

1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239

434 management and conservation challenges of aquatic systems in harbour areas are
435 inherently spatial issues (Valdor et al., 2016). As new spatial data are collected on the
436 distribution and intensity of harbour activities, this will allow for more flexible and adaptive
437 environmental management processes to identify global environmental problems and
438 possible sustainable solutions through an environmental risk assessment approach.

439

440 Future work could improve the current Atlas through the collection and comparison of more
441 data from more harbours across the globe, and it also could test for the robustness of this
442 approach. In addition, new indicators could be developed to improve the method proposed.
443 For example, the navigation and docking of cruise ships or fishing vessels could serve as a
444 complementary indicator for the parameter of risk related to navigation activity (NV), and an
445 international connectivity index of harbours could be an indicator of the potential
446 environmental risks from invasive species.

447 **5. CONCLUSIONS**

448 In this study, we present the first example of an Environmental Risk Assessment (ERA)
449 screening approach to assess the environmental risk on aquatic systems in harbours at
450 global scale. The method implemented in this attempt proposes a semi-quantitative and
451 simple-method to assess the environmental risk on aquatic systems in harbour areas
452 worldwide. The implementation of the method to the 15 diverse harbours has provided
453 sound evidence for the usefulness, versatility and adaptability of the proposed ERA method
454 as a management tool. The method is flexible enough to be applied to any harbour
455 worldwide using international open-databases. The implementation of this method to a wider
456 number of study cases would allow identification of harbours that could improve their
457 environmental management through the implementation of measures with specific
458 indicators. The method lays the foundation of a global atlas for the sustainability of
459 commercial harbours and it provides a powerful tool to facilitate the design of a strategy for
460 the sustainability of the harbour sector at a global level.

1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298

461 **Acknowledgments**

462 In Memoriam of Professor José Antonio Revilla Cortezón (Pepe), former leader of the
463 Environmental Management Group of the University of Cantabria.

464 This work was supported by the World Harbour Project (www.worldharbourproject.org) and
465 its supporters, including The Ian Potter Foundation, the NSW State Government and the
466 SIMS Foundation. Authors would like to thank all the harbour managers worldwide who
467 provided their time to complete the forms to gather relevant information for this study.

468 **Supplementary data**

469 **Appendix A.**

470 The appendix includes the standard form aimed to collected data from each harbour.

471 **Appendix B.**

472 These data include the Google map (.kml) of the Atlas of environmental risk to aquatic
473 systems in the 15 harbours analysed.

474 **REFERENCES**

- 475 AENOR, 2008. UNE 150008:2008. Análisis y evaluación del riesgo ambiental.
476 AENOR. Madrid. 46 pp.
- 477 Antão, P., Calderón, M., Puig, M., Michail, A., Wooldridge, C., Darbra, R.M., 2016.
478 Identification of occupational health, safety, security (OHSS) and
479 environmental performance indicators in port areas. Saf. Sci. 85, 266–275.
480 doi:10.1016/j.ssci.2015.12.031
- 481 Bebianno, M.J., Pereira, C.G., Rey, F., Cravo, A., Duarte, D., D'Errico, G., Regoli,
482 F., 2015. Integrated approach to assess ecosystem health in harbor areas.
483 Sci. Total Environ. 514, 92–107. doi:10.1016/j.scitotenv.2015.01.050
- 484 Brolsma, J.U. 2010. PIANC, The World Association for Waterborne Transport
485 Infrastructure, an association in a changing world, 1885-2010. Brussels,
486 Belgium. Peeters N.V. 175pp.
- 487 Chen J., Chen J., Liao A., Cao X., Chen L., Chen X., He C., Han G., Peng S., Lu
488 M., Zhang W., Tong X., Mills J., 2015 Global land cover mapping at 30m
489 resolution: A POK-based operational approach. ISPRS J. Photogr. Rem.
490 Sens.103, 7-27. doi:10.1016/j.isprsjprs.2014.09.002

1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357

- 491 Cid A., Castanedo S., Abascal A.J., Menéndez M., Medina R., 2014. A high
492 resolution hindcast of the meteorological sea level component for Southern
493 Europe: the GOS dataset. *Clim Dyn.* 43, 7-8, 2167-2184. doi: 10.1007/s00382-
494 013-2041-0
- 495 Cornelissen, G., Pettersen, A., Nesse, E., Eek, E., Helland A., Breedveld, G.D.,
496 2008. The contribution of urban runoff to organic contaminant levels in harbour
497 sediments near two Norwegian cities. *Mar. Pollut. Bull.* 56, 565–573.
498 doi:10.1016/j.marpolbul.2007.12.009
- 499 Darbra, R.M., Ronza, A., Stojanovic, T.A., Wooldridge, C., Casal, J., 2005. A
500 procedure for identifying significant environmental aspects in sea ports. *Mar.*
501 *Pollut. Bull.* 50. doi:10.1016/j.marpolbul.2005.04.037
- 502 EC, 2013. Ports 2030, Gateways for the TransEuropean Transport Network.
503 European Commission. 26 pp.
- 504 EEA, 2005. EEA core set of indicators — guide. In: EEA Technical Report No
505 1/2005. 1725-2237. Luxembourg. 38 pp.
- 506 ESPO-ECOPORTS, 2019. European Port Industry Sustainability Report 2019. 23
507 pp.
- 508 Ferreira, J.G., Wolff, W.J., Simas, T.C., Bricker, S.B., 2005. Does biodiversity of
509 estuarine phytoplankton depend on hydrology? *Ecol. Model.* 187 (4), 513e523.
510 doi: 10.1016/j.ecolmodel.2005.03.013.
- 511 Fortes, J., Silva, C., 2006. Temporal and spatial distribution of dissolved oxygen in
512 the Ria de Aveiro lagoon. *Ecol. Model.* 197 (1e2), 67e88. doi:
513 10.1016/j.ecolmodel.2006.03.012.
- 514 Gamito, S., 2008. Three main stressors acting on the Ria Formosa lagoonal
515 system (Southern Portugal): physical stress, organic matter pollution and the
516 land ocean gradient. *Estuar. Coast. Shelf Sci.* 77, 710e720.
517 doi:10.1016/j.ecss.2007.11.013.
- 518 Gómez, A.G., Juanes, J.A., Ondiviela, B., Revilla, J.A., 2014. Assessment of
519 susceptibility to pollution in littoral waters using the concept of recovery time.
520 *Mar. Pollut. Bull.* 81 (1), 140–148. doi: 10.1016/j.marpolbul.2014.02.004.
- 521 Gómez, A. G., Ondiviela, B., Puente, A., Juanes, J. A., 2015. Environmental risk
522 assessment of water quality in harbor areas: A new methodology applied to
523 European ports. *J. Environ. Manage.* 155, 77–88. doi:
524 10.1016/j.jenvman.2015.01.042
- 525 Gómez, A G., Ondiviela, B., Fernández, M., Juanes, J.A., 2017. Atlas of
526 susceptibility to pollution in marinas. Application to the Spanish coast. *Mar.*
527 *Pollut. Bull.* 114, 239-346. doi:10.1016/j.marpolbul.2016.09.009

1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416

- 528 Gómez, A G., Valdor, P.F., Ondiviela, B., Díaz, J.L., Juanes, J.A., 2019. Mapping
529 the environmental risk assessment of marinas on water quality: The Atlas of
530 the Spanish coast. *Mar. Pollut. Bull.* 139, 355-365.
531 doi:10.1016/j.marpolbul.2019.01.008
- 532 Grifoll, M., Jordá, G., Borja, A., Espino, M., 2010. A new risk assessment method
533 for water quality degradation in harbour domains, using hydrodynamic models.
534 *Mar. Pollut. Bull.* 60, 69–78. doi:10.1016/j.marpolbul.2009.08.030
- 535 Gupta A.K., Gupta S.K., Patil R.S., 2005. Environmental management plan for port
536 and harbour projects. *Clean Techn Environ Policy*. 7 (2), 133-141.
537 doi:10.1007/s10098-004-0266-7
- 538 Halpern, B.S., Walbridge, S., Selkoe, K.A., Kappel, C.V., Micheli, F., D'Agrosa, C.,
539 Bruno, J.F., Kenneth S. C., Ebert, C., Fox, H.E., Fujita, R., Heinemann, D., S.
540 Lenihan, Elizabeth M. P. Madin, Matthew T. Perry, Elizabeth R. Selig, Mark
541 Spalding, H., Steneck, R., Watson, R. , 2008. A Global Map of Human Impact
542 on Marine Ecosystems. *Science*, 319 (5865), 948–952.
543 doi:10.1126/science.1149345
- 544 Hope, B.K., 2006. An examination of ecological risk assessment and management
545 practices. *Environ. Int.* 32, 983–995. doi:10.1016/j.envint.2006.06.005
- 546 ICS, 2018. International chamber of shipping. Annual Review 2018. London. 64 pp.
- 547 ICS, 2019. International chamber of shipping. Annual Review 2019. London. 72 pp.
- 548 IMO, 2004. International Convention for the Control and Management of Ships'
549 Ballast Water and Sediments (BWM). International Maritime Organization.
550 IMO Publisher, London. 7 pp.
- 551 IMO, 2013. IMSBC Code. International maritime solid bulk cargoes code and
552 supplement, 2013 ed. International Maritime Organization. IMO Publisher,
553 London. 558 pp.
- 554 IMO, 2014. IMDG Code. International maritime dangerous goods code. 2014 ed.
555 International Maritime Organization. IMO Publisher, London. 22 pp.
- 556 Intergovernmental Oceanographic Commission of UNESCO, 2017. Information
557 document: International (UN) Decade of Ocean Science for Sustainable
558 Development. "Towards the ocean we need for the future we want". Paris. 23
559 pp.
- 560 Juanes, J. A., Ondiviela, B., Gómez, A. G., Revilla, J.A., 2013. Recommendation
561 for Maritime Works. ROM 5.1-13. Quality of coastal waters in port areas of the
562 Spanish National Port Administrations. Ministry of Public Works, Madrid. 141
563 pp.
- 564 Juanes, J.A., Gómez, A.G., Rubio, S., García-Castrillo, G., Puente, A., Ondiviela, B.,
565 Medina, R. 2020. Santander Bay: Multiuse and multiuser socioecological

1417
1418
1419 566 space. *Regional Studies in Marine Science*, 34-101034.
1420 567 DOI: 10.1016/j.rsma.2019.101034
1421
1422 568 Knights, A.M., Piet, G.J., Jongbloed, R., Tamis, J.E., Robinson, L.A., et al., 2015.
1423 569 An exposure-effect approach for evaluating ecosystem-wide risks from human
1424 570 activities. *ICES J. Mar. Sci.* 72, 1105–1115. doi:10.1093/icesjms/ fsu245.
1425
1426 571 Langanke, T., Rossner, G., Vrscaj, B., Lang, S., Mitchley, J., 2005. Selection
1427 572 and application of spatial indicators for nature conservation at different
1428 573 institutional levels. *J. Nat. Conserv.* 13, 101e114.
1429 574 doi:10.1016/j.jnc.2005.01.005
1430
1431 575 Lethbridge, J.R. 1991. MARPOL 73/78 (International Convention for the Prevention
1432 576 of Pollution from Ships) (English). Infrastructure notes ; no. PS-4. Washington
1433 577 DC : World Bank.
1434 578 [http://documents.worldbank.org/curated/en/860841468330898141/MARPOL-](http://documents.worldbank.org/curated/en/860841468330898141/MARPOL-73-78-International-Convention-for-the-Prevention-of-Pollution-from-Ships)
1435 579 [73-78-International-Convention-for-the-Prevention-of-Pollution-from-Ships](http://documents.worldbank.org/curated/en/860841468330898141/MARPOL-73-78-International-Convention-for-the-Prevention-of-Pollution-from-Ships)
1436
1437
1438 580 Machado, A., 2004. An index of naturalness. *J. Nat. Conserv.* 12, 95e110.
1439 581 doi:10.1016/j.jnc.2003.12.002.
1440
1441 582 Margules, C., Usger, M.B., 1981. Criteria used in assessing wildlife conservation
1442 583 potential: a review. *Biol. Conserv.* 21, 79e109. doi: 10.1016/0006-
1443 584 3207(81)90073-2.
1444
1445 585 OECD, 2003. Environmental Indicators. Development, Measurement and Use. The
1446 586 Organisation for Economic Co-operation and Development, Paris, 37pp.
1447
1448 587 Ondiviela, B., Juanes, J.A., Gómez, A.G., Samano, M.L., Revilla, J.A., 2012.
1449 588 Methodological procedure for water quality management in port areas at the
1450 589 EU level. *Ecol. Indic.* 13, 117–128. doi: 10.1016/ j.envsci.2013.07.001.
1451
1452
1453 590 Parra, N.M., Nagi, A., Kersten, W., 2018. Risk Assessment Methods in Seaports: A
1454 591 Literature Review. Publications of the Hazard Project 24:2018.69 pp.
1455
1456 592 Petrosillo, I., Vassallo, P., Valente, D., Mensa, J.A., Fabiano, M., Zurlini, G., 2010.
1457 593 Mapping the environmental risk of a tourist harbor in order to foster
1458 594 environmental security: objective vs. subjective assessments. *Mar. Pollut. Bull.*
1459 595 60, 1051–1058. <https://doi.org/10.1016/j.marpolbul.2010.01.021>.
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475

1476
1477
1478 596 PIANC, 2011. Towards a Sustainable Waterborne Transportation Industry.
1479 597 EnviCom Task Group 2. September 08, 2011.
1480
1481
1482
1483 598 PIANC, 2019. A Practical Guide to Environmental Risk Management (ERM) for
1484 599 Navigation Infrastructure Projects. EnviCom WG 175. October 24, 2019.
1485
1486
1487
1488 600 PIANC, 2020. Climate Change Adaptation Planning for Ports and Inland
1489 601 Waterways. EnviCom WG 178. January 09, 2020.
1490
1491
1492 602 PIANC, 2006. Environmental Risk Assessment of Dredging and Disposal
1493 603 Operations. PIANC Secretariat General, Brussels.40 pp.
1494
1495 604 Puig, M., Wooldridge, C., Casal, J., Darbra, R.M., 2015. Tool for the identification
1496 605 and assessment of Environmental Aspects in Ports (TEAP). Ocean Coast.
1497 606 Manag. 113, 8–17. doi:10.1016/j.ocecoaman.2015.05.007
1498
1499 607 Ronza, A., Carol, S., Espejo, V., Vílchez, J.A., Arnaldos, J., 2006. A quantitative
1500 608 risk analysis approach to port hydrocarbon logistics. J. Hazard. Mater. 128 (1),
1501 609 10e24. doi:10.1016/j.jhazmat.2005.07.032.
1502
1503 610 Samhouri, J., & Levin, P.S., 2012. Linking land- and sea-based activities to risk in
1504 611 coastal ecosystems. Biol. Conserv. 145, 118–129. doi:
1505 612 10.1016/j.biocon.2011.10.021
1506
1507 613 Smith, A.D.M., Fulton, E.J., Hobday, A.J., Smith, D.C., Shoulder, P., 2007.
1508 614 Scientific tools to support the practical implementation of ecosystem-based
1509 615 fisheries management. ICES J. Mar. Sci. 64, 633–639.
1510 616 doi:10.1093/icesjms/fsm041
1511
1512 617 Steinberg, P.D., Airoldi, L., Banks, J., Leung, K.M.Y., 2016. Introduction to the
1513 618 special issue on the World Harbour Project. Reg. Stud. Mar. Sci., 8 (2), 217-
1514 619 219. doi:10.1016/j.rsma.2016.10.001
1515
1516 620 Strain E, Alexander K, Kienker S, Morris R, Jarvis R, Coleman R, Bollard B, Firth L,
1517 621 Knights A, Grabowski J. 2019.Urban blue: a global analysis of the factors
1518 622 shaping people's perceptions of the marine environment and ecological
1519 623 engineering in harbours. SciTotal Environ 658:1293–1305.
1520 624 <https://doi.org/10.1016/j.scitotenv.2018.12.285>
1521
1522
1523 625 UNCTAD, 2012. Review of Maritime Transport 2012. United Nations. New York
1524 626 and Geneva. United Nations.196 pp.
1525
1526 627 UNCTAD, 2017. Review of maritime transport 2017. United Nations Conference on
1527 628 Trade and Development Review. New York and Geneva.130 pp.
1528
1529
1530
1531
1532
1533
1534

1535
1536
1537 629 UNEP-WCMC, 2016. World Database on Protected Areas. United Nations
1538 630 Environment World Conservation Monitoring Centre - World Commission on
1539 631 Protected Areas (<https://www.protectedplanet.net/>).
1540
1541 632 United Nations, 2015. Transforming our world: the 2030 Agenda for Sustainable
1542 633 Development. General Assembly 70 Session, 16301 (October), 1–35.
1543 634 doi:10.1007/s13398-014-0173-7.2
1544
1545 635 US National Geospatial-Intelligence Agency, 2015. World Port Index, Pub 150. 250
1546 636 pp.
1547
1548 637 Valdor, P.F., Gómez, A.G., Ondiviela, B., Puente, A., Juanes, J.A., 2016.
1549 638 Prioritization maps: the integration of environmental risks to manage water
1550 639 quality in harbor areas. Mar. Pollut. Bull., 111 (1–2) 57-67. doi:
1551 640 10.1016/j.marpolbul.2016.07.028
1552
1553 641 Valdor, P.F., Puente, A., Gómez, A.G., Ondiviela, B., Juanes, J.A., 2017. Are
1554 642 environmental risk estimations linked to the actual environmental impact?
1555 643 Application to an oil handling facility (NE Spain). Mar. Pollut. Bull. 114, 941–
1556 644 951. doi:10.1016/j.marpolbul.2016.10.078
1557
1558 645 Valdor, P.F., Gómez, A.G., Juanes, J.A., Kerléguer, C., Steinberg, P., Tanner, E.,
1559 646 MacLeod, C., Knights, A.M., Seitz, R.D., Airoldi, L., Firth, L.B., Crowe, T.,
1560 647 Chatzinikolaou, E., Smith, A., Arvanitidis, C., Burt, J.A., Brooks, P.R., Ponti,
1561 648 M., Soares-Gomes, A., Ovejero, A., Méndez, G., 2019. A global atlas of the
1562 649 environmental risk of marinas on water quality. Mar. Pollut. Bull. 149, 110661.
1563 650 doi:10.1016/j.marpolbul.2019.110661
1564
1565 651 Yin, J., Falconer, R.A., Che, Y., Probert, S.D., 2000. Water and sediment
1566 652 movements in harbours. Appl. Energy 67, 341e352. PII: S0306-
1567 653 2619(00)00030-1.
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593

Indicators

Parameters

General data
Harbour's name: Postal address: Code: City: Country: web: phone: e-mail address:
Hydromorphological characteristics:
Entrance length (in meters): Average tidal range (in meters): Average depth (in meters): Depth at harbour entrance (in meters):
Human pressures
Number of trade vessels visits per year: Select which activities are developed in the harbour: ☐ Fuel oil and diesel oil supplies ☐ Major repair services ☐ Dangerous/hazardous goods handling Frequency of dredging operations: ☐ Continual ☐ Periodic ☐ No dredging
Environmental management
Number of Environmental Standard: Please, specify what kind of environmental standards (international certifications) are implemented in the marina: Select which environmental measures are implemented in the harbour: Measures: ☐ Garbage disposal ☐ Dirty ballast management ☐ Waste management ☐ Bilge management, Sewer Pump-Out ☐ Oil management Specify any other environmental measure or instrument implemented in the harbour:

Application scope
<ol style="list-style-type: none"> 1. Access to GoogleEarth: https://www.google.es/intl/es/earth/ 2. Introduce the name of the harbour in the seeker. 3. Using Add -> Add a polygon: draw the water surface where port activity takes place. 4. Save the polygon as a .kmz and send it with this questionnaire filled out to: xxxxx.xxxx@unican.es

--

Paloma F. Valdor: Conceptualization, Methodology, Data curation, Resources, Formal analysis, Visualization, Writing - Original Draft, Writing - Review & Editing

Aina G. Gómez: Conceptualization, Methodology, Supervision, Writing - Original Draft, Writing - Review & Editing

Peter Steinberg: Funding acquisition, Writing - Review & Editing

Edwina Tanner: Resources, Data curation, Writing - Review & Editing

Antony M. Knights: Resources, Data curation, Writing - Review & Editing

Rochelle D. Seitz: Resources, Data curation, Writing - Review & Editing

Laura Airoidi: Resources, Data curation, Writing - Review & Editing

Louise B. Firth: Resources, Data curation, Writing - Review & Editing

Christos Arvanitidis: Resources, Data curation, Writing - Review & Editing

Massimo Ponti: Resources, Data curation, Writing - Review & Editing

Eva Chatzinikolaou: Resources, Data curation, Writing - Review & Editing

Paul R. Brooks: Resources, Writing - Review & Editing

Tasman P. Crowe: Resources, Data curation, Writing - Review & Editing

Alison Smith: Resources, Data curation, Writing - Review & Editing

Gonzalo Méndez: Resources, Data curation, Writing - Review & Editing

Aida Ovejero: Resources, Data curation, Writing - Review & Editing

Abilio Soares-Gomes: Resources, Data curation, Writing - Review & Editing

John A. Burt: Resources, Data curation, Writing - Review & Editing

Catriona MacLeod: Resources, Data curation, Writing - Review & Editing

José A. Juanes: Corresponding author, Conceptualization, Methodology, Funding acquisition, Supervision, Project administration, Writing - Review & Editing