

2015-06-16

RANS-VOF Modelling of Wave Energy Converters

Ransley, E

<http://hdl.handle.net/10026.1/13612>

All content in PEARL is protected by copyright law. Author manuscripts are made available in accordance with publisher policies. Please cite only the published version using the details provided on the item record or document. In the absence of an open licence (e.g. Creative Commons), permissions for further reuse of content should be sought from the publisher or author.

RANS-VOF MODELLING OF WAVE ENERGY CONVERTERS

E. Ransley¹, M. Göteman², J. Engström², M. Jakobsen³, M. Eriksson⁵, M. Leijon^{2,4,5},
M. Kramer^{3,6}, M. Hann¹, D. Greaves¹, A. Raby¹, D. Simmonds¹

¹School of Marine Science and Engineering, Plymouth University, edward.ransley@plymouth.ac.uk

²Department of Engineering Sciences, Uppsala University, Sweden, malin.goteman@angstrom.uu.se

³Department of Civil Engineering, Aalborg University, Denmark, mmj@civil.aau.dk

⁴Engineering and the Environment, University of Southampton

⁵Seabased AB

⁶Wave Star A/S

ABSTRACT

This cross-industry/academic project aims to develop a computational tool capable of predicting the behavior of Wave Energy Converter (WEC) and mooring coupled systems in extreme waves. The Numerical Wave Tank (NWT) created employs a fully nonlinear Computational Fluid Dynamics approach to solve the incompressible Reynolds-Averaged Navier-Stokes equations for air and water using a Volume of Fluid treatment of the free surface.

The study compares simulations of two existing WEC designs (Figure 1) with scale-model tank tests. For the Wavestar machine, a point-absorber constrained to pitch motion only [1], results show good agreement with physical measurements of pressure, force and float motion in regular waves. However, the solution in the wake region requires improvement. For the Seabased device, a point-absorber consisting of a moored float and Power Take-Off with limited stroke length, translator and endstop [2], bespoke functionality has been added to the NWT. The 6 Degrees of Freedom float motion and load in the mooring compare well with experiments in large regular waves.

In conclusion, the computational tool developed here is capable of reliably predicting the behaviour of WEC systems and, with some additional parameterisation, could be used to assess the survivability of WEC systems at full-scale before going to the expense of deployment at sea.




Figure 1: Snapshots from simulations with (a) the Wavestar machine, and (b) the Seabased device.

REFERENCES

- [1] Jakobsen, M. M. (2014). 'Wave-structure interactions on point absorber', Technical report, Aalborg University, Denmark.
- [2] Göteman, M., Engström, J., Eriksson, M., Hann, M., Ransley, E., Greaves, D. and Leijon, M. (2015). 'Scale tests on the survivability of point-absorbing wave energy converters - part I', *submitted to Renewable Energy*.