Faculty of Science and Engineering

School of Biological and Marine Sciences

2020-09

## A global approach to mapping the environmental risk of commercial harbours on aquatic systems

### Valdor, P

http://hdl.handle.net/10026.1/15712

10.1016/j.marpol.2020.104051 Marine Policy Elsevier

All content in PEARL is protected by copyright law. Author manuscripts are made available in accordance with publisher policies. Please cite only the published version using the details provided on the item record or document. In the absence of an open licence (e.g. Creative Commons), permissions for further reuse of content should be sought from the publisher or author.

# A global approach to mapping the environmental risk of commercial harbours on aquatic systems

Paloma F. Valdor<sup>a</sup>, Aina G. Gómez<sup>a,m</sup>, Peter Steinberg<sup>b,c</sup>, Edwina Tanner<sup>b</sup>, Antony M.

Knights<sup>d</sup>, Rochelle D. Seitz<sup>e</sup>, Laura Airoldi<sup>f</sup>, Louise B. Firth<sup>d</sup>, Christos Arvanitidis<sup>g</sup>,

Massimo Ponti<sup>f</sup>, Eva Chatzinikolaou<sup>g</sup>, Paul R. Brooks<sup>h</sup> Tasman P. Crowe<sup>h</sup>, , Alison

Smith<sup>e</sup>, Gonzalo Méndez<sup>i</sup>, Aida Ovejero<sup>i</sup>, Abilio Soares-Gomes<sup>i,</sup> John A. Burt<sup>k</sup>, Catriona

MacLeod<sup>I</sup>, José A. Juanes<sup>a,\*</sup>

<sup>a</sup> Environmental Hydraulics Institute, Universidad de Cantabria - Avda. Isabel Torres, 15, Parque Científico y Tecnológico de Cantabria, 39011, Santander, Spain, T:+34.942.20.16.16, palomavaldor@gmail.com, aina.gomez@unican.es, juanesj@unican.es

<sup>d</sup> School of Biological and Marine Sciences, University of Plymouth, Plymouth, U.K., <u>louise.firth@plymouth.ac.uk</u>, <u>antony.knights@plymouth.ac.uk</u>

<sup>e</sup> Virginia Institute of Marine Science, William & Mary, Virginia, U.S.A., <u>seitz@vims.edu</u>, asmith@vims.edu

<sup>f</sup> Department of Biological, Geological and Environmental Sciences and Interdepartmental Research Centre for Environmental Sciences, UO CoNISMa, University of Bologna, Via S. Alberto 163, 48123, Ravenna, Italy, <u>laura.airoldi@unibo.it; massimo.ponti@unibo.it</u>

<sup>g</sup> Institute of Marine Biology, Biotechnology and Aquaculture Hellenic Centre for Marine Research, Attiki, Greece, <u>arvanitidis@hcmr.gr</u>, <u>evachatz@hcmr.gr</u>

<sup>h</sup> UCD Earth Institute and School of Biology and Environmental Science, University College Dublin, Ireland, <u>paul.brooks@ucd.ie; tasman.crowe@ucd.ie</u>

<sup>i</sup> UNESCO Chair in Sustainable Coastal Zone Management, University of Vigo, Vigo, Spain, <u>mendez@uvigo.es</u>, <u>aovejero@uvigo.es</u>

<sup>*j*</sup> Sediment Ecology Laboratory, Marine Biology Department, Federal Fluminense University, Rio de Janeiro, Brazil, <u>abiliosg@id.uff.br</u>.

<sup>k</sup>Center for Genomics and Systems Biology, New York University Abu Dhabi, Abu Dhabi, United Arab Emirates, <u>john.burt@nyu.edu</u>.

<sup>1</sup> Institute for Marine and Antarctic Studies (IMAS), University of Tasmania, Australia, <u>catriona.macleod@utas.edu.au</u>

<sup>m</sup> Balearic Islands Coastal Observing and Forecasting System (SOCIB), Parc Bit, Naorte, Bloc A 2° 3p, 07121 Palma de Mallorca, Spain

\*Corresponding author E-mail addresses: juanesj@unican.es (José A. Juanes)

<sup>&</sup>lt;sup>b</sup> Sydney Institute of Marine Science, 19 Chowder Bay Rd, Mosman NSW 2088, Australia. <u>p.steinberg@unsw.edu.au</u>, Edwina.Tanner@sims.org.au

<sup>&</sup>lt;sup>c</sup> School of BEES, University of New South Wales Sydney, NSW 20152, Australia, <u>p.steinberg@unsw.edu.au</u>


#### 1 A global approach to mapping the environmental risk of harbours on aquatic

#### 2 systems

#### 3 Highlights:

- A method is proposed to assess the environmental risk of commercial harbours on aquatic systems.
- The method is a tool to identify the factors of risk on harbour aquatic systems
- Results obtained from 15 globally distributed harbours are analysed
- Towards the creation of a global atlas of environmental risk of harbours on aquatic systems

#### 10 Graphical abstract:



#### 12 Abstract:

The goal of this paper is to propose a screening method for assessing the environmental risk to aquatic systems in harbours worldwide. A semi-quantitative method is based on environmental pressures, environmental conditions and societal response. The method is flexible enough to be applied to 15 harbours globally distributed through a multinational test using standardised and homogenised open data that can be obtained for any port worldwide. The method emerges as a useful approach towards the foundation of a global

19 environmental risk atlas of harbours that should guide the harbour sector to develop a

20 more globally informed strategy of sustainable development.

Keywords: environmental risk assessment; global atlas; pressure-state-response model;
harbour aquatic systems; harbour management; sustainable development.

#### 24 1. INTRODUCTION

Shipping has an important role in moving about 90% of global trade, which is vital for the continuing and sustainable development of the world economy (ICS, 2018; 2019). The shipping sector is projected to continue to expand in the future with an estimated annual growth rate of 3.2% by 2017-2022 (UNCTAD, 2017). The relevance of this sector for world trade has placed this industry at the centre of a policy debate on globalisation, trade, development and environmental sustainability (UNCTAD, 2012). Harbours are continuing to expand to accommodate the infrastructure required to support growth in the shipping industry (UNCTAD, 2012). This growth increases the likelihood of environmental damage, which, to some extent, is being mitigated by harbour authorities embracing a sustainable development approach (EC, 2013). Shipping, alongside the many other marine activities, generates several threats of varying severity to marine ecosystems (Gómez et al., 2014; Knights et al., 2015; Valdor et al., 2017), and harbours themselves can be some of the most impacted habitats on Earth (Halpern et al., 2008).

The environmental sustainability of harbours needs to be focused on preventing the impoverishment of aquatic systems caused by pollution from commercial ships or other navigation activity. Harbours are guided and regulated by international legislation that aims to limit ecosystem exposure to harmful activities. International bodies, like the International Maritime Organisation (IMO), continue to develop legal frameworks to mitigate environmental harm as a result of commercial shipping (e.g. IMO, 2004; 2013; 2014 or Lethbridge, 1991), and they set the appropriate standards through international treaties and conventions. Others, such as the World Association for Waterborne and Transport Infrastructure (PIANC), provide expert guidance (PIANC, 2019), recommendations (PIANC, 2011) and technical advice (PIANC, 2020) on environmental issues related to both recreational and commercial navigation activity (Brolsma, 2010). The maintenance of high-quality aquatic systems (e.g. by preventing marine pollution) is a permanent and universal goal of these conventions, guidelines and the research developed by these international organisations. Consequently, water quality has been one of the top 10 environmental priorities of the harbour sector over last years (2003-2009) (ESPO-ECOPORTS, 2019).

Scientific research that provides an evidence-based for decision-making related to environmental risk on harbour aquatic systems is conducted by projects like the World Harbour Project (WHP) (www.worldharbourproject.org, Steinberg et al., 2016). This project enhances research and management across major urban harbours. To develop resilient urban harbours, a global network of collaborating scientists works on different topics such as ecological engineering (Strain et al., 2019), environmental management (Valdor et al., 2019), accessible syntheses and summaries of current knowledge (e.g. Juanes et al., 2020). Thus, research programs should be responsible in developing science and communicating findings in an accessible way to a wide range of users to facilitate the design of global strategies. We suggest that global strategies are needed to ensure that harbour managers worldwide are able to assess the environmental risk on aquatic systems using an easy-to-apply and versatile method. In this context, one of the main objectives of global strategies is to provide standardised methods to analyse risk. In this way, data among different harbours are comparable, and their management can be adjusted to the best available practices regarding limiting environmental risk. 

71 However, when global strategies are designed, the harbours' histories, the 72 geomorphological and environmental contexts and the socio-economic settings are very 73 different across the world (Steinberg et al., 2016) and thus may affect approaches to 74 environmental management. In that context, the Environmental Risk Assessment (ERA)

arises as a general management tool that is used worldwide to assess potential effects on the environment due to the exposure to disturbing agents derived from different human activities (e.g. fishery, industry, urban, agricultural or harbour activities, among others) (AENOR, 2008; Hope, 2006; Smith et al., 2007; Samhouri and Levin, 2012; Valdor et al., 2016). Using the ERA approach, the potential effects of environmental hazards on the quality of aquatic systems in harbour areas have been widely studied (e.g. Ronza et al., 2006; Grifoll et al., 2010; Gómez et al., 2015; Ondiviela et al., 2012; Parra et al., 2018), and methods to assess the environmental risks of harbour activities have been proposed (e.g. Gómez et al., 2015; Juanes et al., 2013; Ondiviela et al., 2012; Puig et al., 2015; Valdor et al., 2016). However, worldwide studies to assess the environmental risk of harbour activities on aquatic systems to support global strategies, such as Global Sustainable Development Goals (United Nations, 2015), have not been conducted. 

Harbours around the world implement different environmental management methods that make use of different approaches to the characterisation of systems, use different analytical tools and databases, thus making it challenging to obtain standardised quantitative data globally (PIANC, 2019). For this reason, qualitative and semi-quantitative data analyses are more suitable alternatives when conducting an ERA study at a global scale (Gómez et al., 2019). Moreover, parameters, indicators, and assessment criteria should be carefully selected to integrate the singularities of each specific harbour (Darbra et al., 2005; Gupta et al., 2005). We suggest that, at the same time, the simplicity and low computing cost of the method should allow for wider applicability to harbours of different sizes, hydrodynamic characteristics, harbour uses and pressures or resources to assess environmental challenges.

99 The goal of this paper is to propose a method for mapping the assessment of the
228
229 100 environmental risk of harbours on aquatic systems. This method will be: i) flexible enough
230
231 101 to be applied to any harbour worldwide; ii) open-data dependent; and iii) implemented to lay
232
233 102 the foundation to create a global atlas of environmental risk on aquatic systems of harbours.

The proposed method is tested by applying it to 15 harbours spread across five continents worldwide. The main contributions of this study are: (i) the development of a standard and unified ERA method to assess environmental risk of harbour activities worldwide on aquatic systems (Section 2); (ii) the implementation of the ERA method in 15 harbours around the world (Section 3); and (iii) the discussion of the proposed method and the results obtained in the implementation (Section 4). 

#### 2. MATERIALS AND METHODS

The semi-quantitative method providing an assessment of environmental risk on aquatic systems is based on the Pressure-State-Response (PSR) model defined by Gómez et al. (2019) for marinas. The method comprises the following three steps: i) identification of harbours and data collection; ii) estimation of the risk factors (environmental pressures of harbour activities on the aquatic system, environmental conditions and management responses); and iii) assessment of environmental risk. 

**116** 

#### 2.1 Identification of harbours

Harbours are classified based on the typologies defined by the US National Geospatial-Intelligence Agency (2015) into: i) coastal natural harbours are harbours that are sheltered from the wind and sea due to their location within a natural coastline or occur in the protective lee of an island, cape, reef or other natural barrier, or harbours that are located along a river; ii) coastal breakwater harbours are harbours located behind a human-made breakwater that are constructed to provide shelter or supplement inadequate shelter already provided by natural resources; and iii) natural river harbours are harbours in which slips for vessels have been excavated in the banks obliquely or at right angles to the axis of the stream. 

For this study, general data, hydro-morphological characteristics and environmental management information was gathered globally at all 15 harbours through a standardised form (Supplementary Data. Appendix A) and through other sources of information (e.g., official harbour webpages). 

#### 2.2 Estimation of environmental risk

Environmental risk assessment at the harbour level was based on three factors: i) Pressures from human activities exerted on the environment; ii) State, or the environmental conditions that relate to the quality of the environment; and, iii) Response, or the extent to which the harbour responds to environmental concerns (OECD, 2003) (Eq.1). 

Accordingly and based on Gómez et al., (2019), environmental risk of harbours on aquatic systems was estimated through the following formulas: 

313	136	Ri = Pti x Sti + Rsi	(Eq. 1)
314 315	137	Ri = (NVi + HSi + HOi + CDi) x (SUi + EVi + NAi) + (AMi + Ali)	(Eq. 2)

Where R is the environmental risk, Pt is the Pressure, St is the State and Rs is the Response of an *i* harbour. Pressure is estimated considering the navigation activity (NV), the harbour services (HS), the harbour operation (HO) and the coastal development around the harbour (CD). While, State is estimated by combining the susceptibility (SU), the ecological value (EV) and the naturalness (NA). Finally, Response was estimated through the adopted 

measures (AM) and the Adopted Instruments (AI). 

Estimation of environmental risk was evaluated using a semi-quantitative assessment criteria that was based on a combination of specific indicators, representative of a number of selected parameters for each factor (Table 1). 

Table 1. Parameters, indicators, metrics and criteria assessment to estimate each environmental risk factor. (i: a specific harbour; max: maximum value obtained for a parameter considering all harbours under study; ISO: International Organisation for Standardisation; EMAS: Eco-Management and Audit Scheme; PERS: Port Environmental Review System). Unless specifically indicated by appropriate references to the source paper indicators were originally developed here. 

Factor	Parameter	Indicator and metric (units)	Criteria assessment
Pressures	Navigation Activity (NV)	<b>Density of trade vessels</b> (vessels per year/m <sup>2</sup> ) by dividing vessels per year by the surface water area where the harbour activities take place.	NV <sub>i</sub> /NV <sub>max</sub> [0-1]

		Harbour Services (HS)	(1) or absence (0) of fuel oil and diesel oil supplies, major repair services and dangerous/hazardous goods handling within the area where the harbour activities take place (Valdor et al., 2016).	HS <sub>i</sub> /HS <sub>max</sub> [0-1]	
		Harbour Operation (HO)	<i>Dredging probability,</i> frequency of dredging operations.	Continual Periodic None	1.0 0.5 0.0
		Coastal Development (CD)	<i>Land uses</i> developed in a 1- km buffer distance around the harbour (worst case scenario) (Gómez et al., 2019).	Artificial Agricultural Natural - Other uses	1.0 0.5 0.0
		Susceptibility (SU)	<i>Flushing capacity</i> of the water volume where harbour activities take place, combining hydrodynamic and morphological characteristics through the Complexity Tidal Range Index (CTRI*) (Gómez et al., 2017).	CTRI* <sub>i</sub> /CTRI* <sub>max</sub> [0-1]	
5	State	Ecological Value (EV)	Number of <b>Protected areas</b> (#) in a 1-km buffer distance around the surface water area where the harbour activities take place (Gómez et al., 2019).	EV <sub>i</sub> /EV <sub>max</sub> [0-1]	
		Naturalness (NA)	<i>Alteration by hydro- morphological pressures</i> in a harbour's environment (harbour's typology) (US National Geospatial- Intelligence Agency, 2015)	Open Roadstead Natural (Coastal or River) Coastal Breakwater/ River Basin Tide Gates (Coastal or River)/Canal or Lake	1.0 0.75 0.5 0.0
	Response	Adopted Measures (AM)	Number of <b>adopted</b> <b>measures</b> (#) to reduce the pressure of human activities on the environment (garbage disposal, dirty ballast management, etc.) (Gómez et al., 2019).	AM <sub>i</sub> /AM <sub>max</sub> [0-1]	<u> </u>
152		Adopted Instruments (Al)	Number of <b>adopted</b> <b>standards</b> (#) to improve the environmental performance (ISO 14001, EMAS, PERS, others.) (Gómez et al., 2019).	Al <sub>i</sub> /Al <sub>max</sub> [0-1]	

the harbour's infrastructures or the natural elements that conform the harbour's entry (m) and R is the medium

tidal range (m) (Gómez et al., 2017). 

158 The range of the potential values of all parameters were normalised (varying from 0 to1) by 159 dividing the observed value by the maximum value, after discarding outliers for each 160 parameter with values greater than  $x \Box \pm 3$ ·SD (Gómez et al., 2019).

#### 161 2.3. Environmental Risk Assessment

To assess the environmental risk to the harbour's aquatic systems, the results of pressure and state factors were classified into four categories (1 to 4), while the response factor was categorised by assigning one of either values: 0 or 4 (Table 2, Eq. 2). Levels separating the different categories were established for all harbours under study using the 25th, 50th and 75th percentile values, with the 50th percentile value used as the threshold between optimal and insufficient response (Table 2).

440 168


Table 2. Criteria to assess Pressures (Pr<sub>i</sub>), State (St<sub>i</sub>) and Response (Rs<sub>i</sub>) categories from study site
results (VL: Very low; L: low; M: moderate; H: high; P25: 25th Percentile; P50: 50th Percentile; P75:
75th Percentile).


Factor	Category	Criteria	Thresholds
Pressures (Pr)	VL (1)	Pri ≤ P25	Pri ≤ 2.11
	L (2)	P25 < Pri ≤ P50	2.11 < Pri ≤2.51
	M (3)	P50 < Pri ≤ P75	2.51 < Pri ≤ 2.58
	H (4)	Pri > P75	Pri > 2.58
	VL (1)	Sti ≤ P25	Sti ≤ 0.95
State (St)	L (2)	P25 < Sti ≤ P50	0.95 < Sti ≤ 1.10
	M (3)	P50 < Sti ≤ P75	1.10 < Sti ≤ 1.37
	H (4)	Sti > P75	Sti > 1.37
Response (Rs)	Optimal (0)	Rsi ≥ P50	Rsi ≥ 0.75
	Insufficient (4)	Rsi < P50	Rsi < 0.75

174 Obtained scores at the factor level (Table 2) were used to estimate the environmental risk

175 of each harbour through Eq. 1. Based on the environmental risk value (Eq. 1), each harbour

was classified considering three categories: (i) high-risk harbour ( $Ri \ge 12$ ), (ii) moderate-risk harbour ( $6 \le Ri < 12$ ), (iii) low-risk harbour ( $1 \le Ri < 6$ ). 3. RESULTS 3.1. Identification of harbours The twenty-seven partners of World Harbour Project network were invited to participate to test the developed ERA method (Steinberg et al., 2016). Fifteen WHP partners were able to encourage harbour managers from their respective cities to participate and to gather the needed information. WHP partners contacted harbour managers by email or phone, and meetings were conducted when necessary. The fifteen harbours, where the developed ERA method was tested, spanned Europe (Dublin, Heraklion, Plymouth, Santander, Ravenna and Vigo), Australasia (Ashdod, Auckland, Darwin, Hobart, Hong Kong, Qingdao and Sydney) and the Americas (Baltimore and Rio de Janeiro) (Figure 1). "Coastal natural harbour" was the typology best represented by seven harbours (Rio de Janeiro, Qingdao, Hong Kong, Santander, Vigo, Darwin and Sydney), followed by "coastal breakwater harbours" represented by four harbours (Ashdod, Dublin, Heraklion, and Ravenna) and "natural river harbours" represented by four harbours (Baltimore, Plymouth, Auckland and Hobart) (Figure 1). 






The standardised form (Appendix A) was used to gather information from harbour managers. Harbour managers sent the filled-in form through email to their respective local WHP partner. In addition to consulting with harbour managers, where possible, data collected was cross-checked using global, national (e.g. puertos.es) and local resources or was specifically sourced from each harbour (e.g. the official web page of each harbour). Using these sources of information, a database of metrics was generated for each harbour.

#### 3.2. Estimation of environmental risk

The environmental risk assessment process provided explicit information on the parameters of risk. To define the spatial scope, a polygon of the surface area of the water where harbour activities take place was first digitalized using ArcGIS software. Harbour managers were asked to approve the delimitation of these areas. The resulting polygons indicated harbour surface-water areas (Supplementary data. Appendix B). The tools "extract by mask" and "Clip" from the ArcGIS software were used to recognize both land uses and protected areas in 1-km buffer around each harbour, using Globe Land 30 (Chen et al., 2015) and World Database on Protected Areas (UNEP-WCMC, 2016), respectively. Mean tidal range (R, m), as a hydrodynamic characteristic, was calculated from the GOS dataset (Cid et al., 2014); morphological characteristics were estimated for each harbour using ArcGIS techniques, including area (A, m<sup>2</sup>), applying the "calculate geometry" tool; length (L, m) and entrance width (e, m), using the "minimum bounding geometry" tool (Gómez et al., 2017). 

Pressures: Normalised values of navigation activity (NV) were extremely variable among the studied harbours. Ashdod had the highest density of trade vessels (1), followed by Ravenna (0.18), Dublin (0.16), Qingdao (0.15) and Rio de Janeiro (0.11), while the other harbours showed normalised values lower than 0.07 (Figure 2, NV). Most harbour areas showed the maximum value of Harbour Services (HS), since 10 of the 15 study sites develop fuel oil and diesel oil supplies, major repair services and dangerous or hazardous goods handling activities (Figure 2, HS). Exceptions to this were Hobart and Plymouth, where fuel oil supply 

and major repairs are not developed, and Heraklion and Ravenna, where dangerous or hazardous goods handling is not carried out. Harbour Operation (HO) was estimated through dredging activities, which is are periodic operation in most of the harbours (0.5) apart from Ashdod and Hong Kong, where continual dredging operations are undertaken (1), and Hobart and Qingdao, where dredging operations are not carried out (Figure 2, HO). Normalised Coastal development scored 1 in nearly all the harbours, since the land use around the harbours was mainly artificial (urban, mining or industrial). Only one harbour (Darwin) presented natural land uses in its surroundings (Figure 2, CD). 



632230Figure 2. Representation of normalised values of the parameters applied for the estimation of the633633634231environmental pressures (Pressures) at each of the 15 studied harbours

State: Susceptibility (SU, a measure of flushing capacity) was the most variable parameter of State in all the 15 harbours studied (Figure 3, SU) as it is related to the cleaning capacity of the water volume, which combines hydrodynamic and morphological characteristics at the harbour level. The main characteristics of the harbours that were responsible for this variability were the differences in water surface area (~0.8 km<sup>2</sup> in Plymouth, to 36.73 km<sup>2</sup> in 

Darwin), the minimum distance between the elements that conform the harbour's entry (~0.2 km in Ravenna to ~316 km in Darwin) and the variability in tidal ranges (microtidal in the Mediterranean to a 5 m tidal range in Plymouth). Regarding the Ecological Value (EV), the number of protected areas located in a 1-km buffer distance-around the harbour's water surface area varied among the different harbours: 0 (five harbours), 1 (four harbours), 2 (two harbours), 4 (two harbours) and 6 (two harbours) (Figure 3, EV). Conversely, naturalness (NA) showed similar values at all harbours, with most of them (11) with a normalised NA value of 0.75 and only 4 harbours with 0.5 (Figure 3, NA). 





Figure 3. Representation of normalised values of the parameters applied for the estimation of
environmental conditions (State) at each of the 15 studied harbours.

Response: All studied harbours implemented a minimum of 3 Adopted Measures (AM) to reduce the pressures of human activities on the environment (AM normalised value  $\leq 0.5$ ), with 8 being the maximum number of measures applied in Qingdao and Baltimore (1 AM normalised value) (Figure 4, AM). A higher variability was registered in the number of Adopted Instruments (AI), with eight harbours where no instruments to achieve international

standards were applied, four harbours where 1 was adopted, two harbours where 2
instruments were applied and one harbour where 3 international instruments were applied
(Figure 4, AI).



### 259 Figure 4. Representation of normalised values of the parameters applied for the estimation of level 260 of response (Response), at each of the 15 studied harbours.

#### 3.3. Environmental risk assessment

In terms of Pressure categories, two harbours were assessed to have high environmental pressure with four harbours assessed as being moderate. This was followed by a total of six harbours that were assessed as having low environmental pressures and, finally, three harbours with very low associated pressures (Figure 5, Pressures in blue bars). Regarding the State factor, four harbours were classified within the high category, with three harbours showing moderate environmental conditions and a total of eight harbours within the low and very-low categories (Figure 5, State in yellow bars). Finally, 7 of the 15 studied harbours showed insufficient environmental management, while 8 harbours presented an optimal level of management Response (Figure 5, Response in green bars). 

The most frequent category of risk was moderate; 8 of the 15 harbours studied presented moderate risk, 5 harbours presented low risk, while 2 harbours presented a high environmental risk to aquatic systems (Figure 5, Environmental risk in red bars).




Figure 5. Graphical representation of categorised risk factors (Pressures, State and Response) and
categorised environmental risk to aquatic systems at each of the 15 studied harbours.

279 Results of environmental risk to aquatic systems of harbours, based on this study's results280 are shown in Supplementary data Appendix B.

 807
 808
 281
 4. DISCUSSION

### 809<br/>8102824.1 Why this ERA method?: The conceptual model

From a conceptual point of view, the Pressure-State-Response (PSR) model (OECD, 2003) is used as a framework to select indicators that assess environmental risk at the harbour level, based on Gómez et al., (2019). Moreover, the Driving force-Pressure-State-Impact-Response (DPSIR) model (EEA, 2005) is integrated in the PSR model to define specific indices of Pressure, State and Response. These indices group and classify a small number of indicators (Figure 6). 

From a practical point of view, the selection of general-purpose indicators for global assessments was complex because of the need to obtain homogeneous, objective and systematic, open and publicly available data and information on a series of diverse parameters from analogous entities (harbours) that are under different socio-ecological contexts from all over the world. Indicators were selected based on: i) the complementarity and non-redundancy of indicators in their representation of risk factors; ii) the possibility of finding available and homogeneous data from harbours worldwide, and iii) state-of-the-art and previous studies. 

Driving forces describe the social, demographic and economic development within a given harbour (EEA, 2005). Based on the conceptual model presented (Figure 6), indicators selected to estimate the environmental pressures include the four main driving forces relevant to the harbour areas (navigation, harbour services, harbour operation and coastal development). Navigation activity, estimated as the number of trade vessel visits per year by a water-surface area of a harbour, was selected, as it has been identified in previous works as a representative environmental stressor (Antão et al., 2016) and it is easily accessible from institutional statistics (e.g. Eurostat, or individual webpages of harbours). Regarding Harbours Services (HS), two indicators were selected: i) major repair services (shipyards, ship repair or painting, etc.) that generate chemical wastes (heavy metals, PAHs and antifoulants), which can pose a risk to aquatic organisms inhabiting harbour areas (Bebianno et al., 2015); and ii) dangerous/hazardous goods handling defined by IMO codes (IMO, 2014), which were previously considered in ERA mapping studies on harbour systems (e.g. Valdor et al., 2016). Furthermore, dredging, one of the most important operations and maintenance activities within harbours (PIANC, 2006), and dominant land use in the surrounding area, served as proxies of the external influences on water quality (Cornelissen et al., 2008). 

Indirect or direct pressures are identified by each driving force (Gómez et al., 2019). The identified pressures produce impacts altering the state of the environment (Ondiviela et al., 2013; Petrosillo et al., 2010). State factor of risk considers three important aspects of the harbour's environment: susceptibility, ecological value and naturalness. From the eight pressure indicators proposed in the conceptual model (Figure 6), there are three related to quality of the aquatic system (chemical quality, physico-chemical quality and biological quality) that require periodic monitoring and systematic evaluation. Since each country applies different monitoring and evaluation systems (in terms of thresholds, frequency, etc.), the susceptibility to water and sediment contamination was considered as a standard representative indicator of the quality of the aquatic system of harbours worldwide, assuming a significant relationship between flushing capacity and water quality in littoral areas (Ferreira et al., 2005; Fortes and Silva., 2006; Gómez et al, 2014; Yin et al., 2000). This assumption was previously used for ERA in marinas (Gómez et al., 2017) and harbours (Gómez et al., 2015). The harbour's ecological value considered that the greater the protected area in the vicinity of the harbours is, the greater the biodiversity and ecological processes that maintain that system (Gómez et al., 2015; Langanke et al., 2005; Margulles and Usger, 1981). Finally, their 'naturalness' (Machado, 2004) was estimated using the harbour typology (US National Geospatial-Intelligence Agency, 2015) as a surrogate of number and dimensions of hydro-morphological pressures at the marina level typology (Gamito, 2008; Gómez et al., 2019).

**336** 

The response factor to environmental risk was used to integrate the actions and reactions, intended to mitigate, adapt to or prevent human-induced negative effects on the environment that could be applied to minimize the impacts of driving forces and improve the state of aquatic ecosystems (OECD, 2003). Responses may arise from different sectors, such as those in social, technical or institutional (i.e. local, national or international administrations) realms (Figure 6). Among all of them, institutional responses are the option that integrates a greater number of fields involving social responses (awareness campaigns), institutional

responses (policy and strategies) and technical responses (research). For this reason, the
implementation of different kinds of well-known international measures (e.g., garbage
disposal, oil recycling, ballast water management, among others) and international
standards (e.g. EMAS, ISO, PERS, among others) was considered an appropriate indicator
to estimate the response factor.




Figure 6. Conceptualisation of the causal links between main driving forces, pressures, impacts, state andresponse of aquatic systems in harbours.

**352** 

#### 353 4.2 The global implementation

Based on this study's results, the method used provides a tool to standardize the assessment of environmental risk to aquatic systems at a global scale (Supplementary data Appendix B). However, a question arose from this implementation: Are the PSR and DPSIR scenarios of the study sites representative of the environmental risks of harbours globally? ERA results showed that most of the study areas had a moderate risk but included significant variability of environmental pressures, environmental conditions and societal responses. However, results showed differences at the indicator level in those harbours within the same 

category of risk. For instance, Hobart showed a moderate environmental risk on the aquatic system due to a combination of high vulnerability (high naturalness but a moderate ecological value of the surroundings) with a high score of environmental management (due to the low number of adopted measures and none of the international standards implemented). Heraklion showed a moderate risk on the aquatic system even though they were adopting a good number of environmental measures (above the average) to reduce the pressure of human activities on the environment because no international environmental management instruments were applied. In other cases, the higher susceptibility (Baltimore) or the higher ecological value (Ravenna), were the parameters of risk that penalised the result for these harbours. Identification of such risk parameters allows for the targeted application of more preventive and corrective management actions to help reduce environmental risk to aquatic systems for those specific harbours. 

 373 Therefore, from a practical perspective, the environmental risk assessment method can be
 1031 1032
 374 used as a tool to proactively identify the most important factors of risk on which to apply
 375 actions that allow for environmental improvements in each.

For this, expert knowledge on environmental risk is not strictly necessary, but a deep understanding on the environment harbour characteristics is needed. These data are controlled and known by harbour managers. In Section 2, practical steps are described considering parameters, indicators, metrics and criteria to estimate each risk factor. The pathway to apply the ERA method to an individual harbour include the collection of the information needed and the calculation of parameters for each risk factor. A standardized form to gather the information is provided in Appendix A and calculations described at Section 2 are easy to apply with a basic knowledge of spatial analysis using geographical information systems.

1053<br/>1054385Once applied, the method can be used to detect which harbours should apply environmental<br/>10541055<br/>1056386measures or/and international standards to improve their management of aquatic systems,<br/>10561057<br/>1057387based on the highest standards of environmental quality applied around the world. An<br/>example of this is shown in Figure 7, which represents the hypothetical case in which the 15

harbours analysed for this implementation applying eight environmental measures (such as garbage disposal, dirty ballast management, waste management, bilge management, sewer pump-out, oil management) and 1 international standard (Figure 7). As all harbours apply the maximum number of environmental measures and standard certifications, the value of the response factor is 0 (optimal response) for all the harbours analysed. For this reason, the green bars are not observed in Figure 7. 




Figure 7. Graphical representation of a hypothetical situation at each of the 15 studied harbours
with reduced categorised risk factors (pressures, state and responses) by the application of at least
4 environmental measures and 1 international standard and categorised environmental risk to
aquatic systems.

In this case, one harbour continues to show high risk, five harbours show moderate risk while the other nine show a low environmental risk on the aquatic system. The screening capacity of this tool may address the global challenge of standardizing methods that produce comparable risk assessments of high-level entities (e.g. harbours) at large spatial scales. However, if the harbours applying the environmental measures and certifications do not obtain a low value of environmental risk, they should then focus their efforts on reducing the 

environmental risk factors that are penalizing the final value of environmental risk. This is the case in Hong Kong, which has high pressures due to the presence of intense navigation activity (NV), the harbour services (HS) provided in the harbour, the continual dredging activity (DG) in the harbour area and the Coastal development (CD) in their surroundings. Baltimore is also highly susceptible probably due to the morphological characteristics of the harbour area, which is very difficult to change from an environmental management standpoint. In these cases, socio-economic issues should also be incorporated into a long-term sustainability or management plan, which must assess the disadvantages and benefits that may result from modifying factors that penalized the final value of the environmental risk. 

1144 416

To the extent that harbours collaborate by providing the necessary information for the calculation of environmental risk, it will be possible to create a global atlas of risk. Collaboration by harbours will be feasible as long as the global atlas were understood as a participatory process towards the sustainability of aquatic systems, recalling the adoption of the 2030 Agenda and its Sustainable Development Goals (SDG, in particular SDG 14) and the more recent resolution of the UN on the Decade for Ocean Sciences (2021-30), which will provide a unifying framework across the UN system to enable countries to achieve all of their ocean-related Agenda 2030 priorities (IOC, 2017). 

<sup>1161</sup> 425 

The global atlas developed by using the method presented herein would introduce valuable bring the elements of judgment to guide managers involved in decision-making (AENOR, 2008) towards the sustainability of aquatic systems in harbour areas, as well as to design the first global strategy for sustainability related to the water quality at a global level. Sustainable development goal (SDG) 14 in the UN 2030 Agenda requires to "conserve and sustainably use the oceans, seas and marine resources for sustainable development" (United Nations, 2015). Global Sustainable development goals require global analysis of the problems presented and definition of global strategies to resolve them. Many critical 

management and conservation challenges of aquatic systems in harbour areas are inherently spatial issues (Valdor et al., 2016). As new spatial data are collected on the distribution and intensity of harbour activities, this will allow for more flexible and adaptive environmental management processes to identify global environmental problems and possible sustainable solutions through an environmental risk assessment approach. 

Future work could improve the current Atlas through the collection and comparison of more data from more harbours across the globe, and it also could test for the robustness of this approach. In addition, new indicators could be developed to improve the method proposed. For example, the navigation and docking of cruise ships or fishing vessels could serve as a complementary indicator for the parameter of risk related to navigation activity (NV), and an international connectivity index of harbours could be an indicator of the potential environmental risks from invasive species. 

#### 5. CONCLUSIONS

In this study, we present the first example of an Environmental Risk Assessment (ERA) screening approach to assess the environmental risk on aquatic systems in harbours at global scale. The method implemented in this attempt proposes a semi-quantitative and simple-method to assess the environmental risk on aquatic systems in harbour areas worldwide. The implementation of the method to the 15 diverse harbours has provided sound evidence for the usefulness, versatility and adaptability of the proposed ERA method as a management tool. The method is flexible enough to be applied to any harbour worldwide using international open-databases. The implementation of this method to a wider number of study cases would allow identification of harbours that could improve their environmental management through the implementation of measures with specific indicators. The method lays the foundation of a global atlas for the sustainability of commercial harbours and it provides a powerful tool to facilitate the design of a strategy for the sustainability of the harbour sector at a global level. 

#### 461 Acknowledgments

- 462 In Memoriam of Professor José Antonio Revilla Cortezón (Pepe), former leader of the
   <sup>7</sup> 463 Environmental Management Group of the University of Cantabria.
- 49 464 This work was supported by the World Harbour Project (www.worldharbourproject.org) and
- 465 its supporters, including The Ian Potter Foundation, the NSW State Government and the
- $_{54}^{55}$  466 SIMS Foundation. Authors would like to thank all the harbour managers worldwide who
- $\frac{1}{2}$  467 provided their time to complete the forms to gather relevant information for this study.
- 58 468 Supplementary data
- 469 Appendix A.
- $\frac{1}{3}$  470 The appendix includes the standard form aimed to collected data from each harbour.
- 265 471 **Appendix B.**
- 472 These data include the Google map (.kml) of the Atlas of environmental risk to aquatic
- <sup>69</sup> 473 systems in the 15 harbours analysed.

#### 71 474 **REFERENCES**

- AENOR, 2008. UNE 150008:2008. Análisis y evaluación del riesgo ambiental.
   AENOR. Madrid. 46 pp.
- Antão, P., Calderón, M., Puig, M., Michail, A., Wooldridge, C., Darbra, R.M., 2016.
  Identification of occupational health, safety, security (OHSS) and
  environmental performance indicators in port areas. Saf. Sci. 85, 266–275.
  doi:10.1016/j.ssci.2015.12.031
- 481 Bebianno, M.J., Pereira, C.G., Rey, F., Cravo, A., Duarte, D., D'Errico, G., Regoli,
  482 F., 2015. Integrated approach to assess ecosystem health in harbor areas.
  483 Sci. Total Environ. 514, 92–107. doi:10.1016/j.scitotenv.2015.01.050
- 484 Brolsma, J.U. 2010. PIANC, The World Association for Waterborne Transport
  485 Infrastructure, an association in a changing world, 1885-2010. Brussels,
  289 486 Belgium. Peeters N.V. 175pp.
- 1291487Chen J., Chen J., Liao A., Cao X., Chen L., Chen X., He C., Han G., Peng S., Lu1292488M., Zhang W., Tong X., Mills J.,2015 Global land cover mapping at 30m1293489resolution: A POK-based operational approach. ISPRS J. Photogr. Rem.1294490Sens.103, 7-27. doi:10.1016/j.isprsjprs.2014.09.002


1299		
1300		
1301	491	Cid A., Castanedo S., Abascal A.J., Menéndez M., Medina R., 2014. A high
1302	492	resolution hindcast of the meteorological sea level component for Southern
1303	493	Europe: the GOS dataset. Clim Dyn.43, 7-8, 2167-2184. doi: 10.1007/s00382-
1304	494	013-2041-0
1305	434	015-2041-0
1306	405	Compliance O Detterror A Name E Fall E Helland A Dreadwald O D
1307	495	Cornelissen, G., Pettersen, A., Nesse, E., Eek, E., Helland A., Breedveld, G.D.,
1308	496	2008. The contribution of urban runoff to organic contaminant levels in harbour
1309	497	sediments near two Norwegian cities. Mar. Pollut. Bull. 56, 565–573.
1310	498	doi:10.1016/j.marpolbul.2007.12.009
1311		
1312	499	Darbra, R.M., Ronza, A., Stojanovic, T.A., Wooldridge, C., Casal, J., 2005. A
1313	500	procedure for identifying significant environmental aspects in sea ports. Mar.
1314	501	Pollut. Bull. 50. doi:10.1016/j.marpolbul.2005.04.037
1315		· · · · · · · · · · · · · · · · · · ·
1316	502	EC, 2013. Ports 2030, Gateways for the TransEuropean Transport Network.
1317	503	European Commission. 26 pp.
1318	505	
1319	504	FEA 2005 FEA care act of indicators and do Inv FEA Technical Depart Na
1320	504	EEA, 2005. EEA core set of indicators — guide. In: EEA Technical Report No
1321	505	1/2005. 1725-2237. Luxembourg. 38 pp.
1322		
1323	506	ESPO-ECOPORTS, 2019. European Port Industry Sustainability Report 2019. 23
1324	507	pp.
1325		
1326	508	Ferreira, J.G., Wolff, W.J., Simas, T.C., Bricker, S.B., 2005. Does biodiversity of
1327	509	estuarine phytoplankton depend on hydrology? Ecol. Model. 187 (4), 513e523.
1328	510	doi: 10.1016/j.ecolmodel.2005.03.013.
1329	010	doi: 10.1010/j.000/m0d01.2000.001010.
1330	511	Fortes, J., Silva, C., 2006. Temporal and spatial distribution of dissolved oxygen in
1331	512	
1332		the Ria de Aveiro Iagoon. Ecol. Model. 197 (1e2), 67e88. doi:
1333	513	10.1016/j.ecolmodel.2006.03.012.
1334		
1335	514	Gamito, S., 2008. Three main stressors acting on the Ria Formosa lagoonal
1336	515	system (Southern Portugal): physical stress, organic matter pollution and the
1337	516	land ocean gradient. Estuar. Coast. Shelf Sci. 77, 710e720.
1338	517	doi:10.1016/j.ecss.2007.11.013.
1339		
1340	518	Gómez, A.G., Juanes, J.A., Ondiviela, B., Revilla, J.A., 2014. Assessment of
1341	519	susceptibility to pollution in littoral waters using the concept of recovery time.
1342	520	Mar. Pollut. Bull. 81 (1), 140–148.doi: 10.1016/j.marpolbul.2014.02.004.
1343	020	
1343	521	Gómez, A. G., Ondiviela, B., Puente, A., Juanes, J. A., 2015. Environmental risk
1344		
1345	522	assessment of water quality in harbor areas: A new methodology applied to
1340	523	European ports. J. Environ. Manage. 155, 77–88. doi:
1347	524	10.1016/j.jenvman.2015.01.042
1348		
1349	525	Gómez, A G., Ondiviela, B., Fernández, M., Juanes, J.A., 2017. Atlas of
1351	526	susceptibility to pollution in marinas. Application to the Spanish coast. Mar.
1352	527	Pollut. Bull.114, 239-346. doi:10.1016/j.marpolbul.2016.09.009
1353		
1353		
1355		
1355		
1357		
1007		


1358		
1359		
1360	528	Gómez, A G., Valdor, P.F., Ondiviela, B., Díaz, J.L., Juanes, J.A., 2019. Mapping
1361	529	the environmental risk assessment of marinas on water quality: The Atlas of
1362		
1363	530	the Spanish coast. Mar. Pollut. Bull.139, 355-365.
1364	531	doi:10.1016/j.marpolbul.2019.01.008
1365		
1366	532	Grifoll, M., Jordá, G., Borja, A., Espino, M., 2010. A new risk assessment method
1367	533	for water quality degradation in harbour domains, using hydrodynamic models.
	534	Mar. Pollut. Bull. 60, 69–78. doi:10.1016/j.marpolbul.2009.08.030
1368	554	Mai. Poliul. Dull. 00, 09–70. 001.10.1010/j.11a1polbul.2009.00.050
1369		
1370	535	Gupta A.K., Gupta S.K., Patil R.S., 2005. Environmental management plan for port
1371	536	and harbour projects. Clean Techn Environ Policy.7 (2), 133-141.
1372	537	doi:10.1007/s10098-004-0266-7
1373		
1374	538	Halpern, B.S., Walbridge, S., Selkoe, K.A., Kappel, C.V., Micheli, F., D'Agrosa, C.,
1375		
1376	539	Bruno, J.F., Kenneth S. C., Ebert, C., Fox, H.E., Fujita, R., Heinemann, D., S.
1377	540	Lenihan, Elizabeth M. P. Madin, Matthew T. Perry, Elizabeth R. Selig, Mark
1378	541	Spalding, H., Steneck, R., Watson, R., 2008. A Global Map of Human Impact
	542	on Marine Ecosystems. Science, 319 (5865), 948–952.
1379	543	doi:10.1126/science.1149345
1380	• • •	
1381	E A A	Hone R.K. 2006. An examination of coolegical rick approximant and management
1382	544	Hope, B.K., 2006. An examination of ecological risk assessment and management
1383	545	practices. Environ. Int. 32, 983–995. doi:10.1016/j.envint.2006.06.005
1384		
1385	546	ICS, 2018. International chamber of shipping. Annual Review 2018. London. 64 pp.
1386		
1387	547	ICS, 2019. International chamber of shipping. Annual Review 2019. London.72 pp.
1388	047	
1389	E 4 0	INIO 2004 International Convention for the Control and Management of Chine?
1390	548	IMO, 2004. International Convention for the Control and Management of Ships'
	549	Ballast Water and Sediments (BWM). International Maritime Organization.
1391	550	IMO Publisher, London.7 pp.
1392		
1393	551	IMO, 2013. IMSBC Code. International maritime solid bulk cargoes code and
1394	552	supplement, 2013 ed. International Maritime Organization. IMO Publisher,
1395	553	London. 558 pp.
1396	555	London. 556 pp.
1397		
1398	554	IMO, 2014. IMDG Code. International maritime dangerous goods code. 2014 ed.
1399	555	International Maritime Organization. IMO Publisher, London.22 pp.
1400		
1401	556	Intergovernmental Oceanographic Commission of UNESCO, 2017. Information
1402	557	document: International (UN) Decade of Ocean Science for Sustainable
1402		
	558	Development. "Towards the ocean we need for the future we want". Paris.23
1404	559	pp.
1405		
1406	560	Juanes, J. A., Ondiviela, B., Gómez, A. G., Revilla, J.A., 2013. Recommendation
1407	561	for Maritime Works. ROM 5.1-13. Quality of coastal waters in port areas of the
1408	562	Spanish National Port Administrations. Ministry of Public Works, Madrid.141
1409		
1410	563	pp.
1411		
1412	564	Juanes, J.A., Gómez, A.G., Rubio, S., García-Castrillo, G., Puente, A., Ondiviela, B.,
1413	565	Medina, R. 2020. Santander Bay: Multiuse and multiuser socioecological
1414		
1414		
1416		


1417		
1418		
1419	566	space. Regional Studies in Marine Science, 34-101034.
1420	567	DOI: 10.1016/j.rsma.2019.101034
1421		
1422	568	Knights, A.M., Piet, G.J., Jongbloed, R., Tamis, J.E., Robinson, L.A., et al., 2015.
1423	569	An exposure-effect approach for evaluating ecosystem-wide risks from human
1424	570	activities. ICES J. Mar. Sci. 72, 1105–1115. doi:10.1093/icesjms/ fsu245.
1425	010	
1426	571	Langanke, T., Rossner, G., Vrscaj, B., Lang, S., Mitchley, J., 2005. Selection
1427		
1428	572	andapplication of spatial indicators for nature conservation at different
1429	573	institutional levels. J. Nat. Conserv. 13, 101e114.
1430	574	doi:10.1016/j.jnc.2005.01.005
1431		
1432	575	Lethbridge, J.R. 1991. MARPOL 73/78 (International Convention for the Prevention
1433	576	of Pollution from Ships) (English). Infrastructure notes ; no. PS-4. Washington
1434	577	DC : World Bank.
1435	578	http://documents.worldbank.org/curated/en/860841468330898141/MARPOL-
1436	579	73-78-International-Convention-for-the-Prevention-of-Pollution-from-Ships
1437		
1438	580	Machado, A., 2004. An index of naturalness. J. Nat. Conserv. 12, 95e110.
1439	581	doi:10.1016/j.jnc.2003.12.002.
1440		
1441	582	Margules, C., Usger, M.B., 1981. Criteria used in assessing wildlife conservation
1442	583	potential: a review. Biol. Conserv. 21, 79e109. doi: 10.1016/0006-
1443	584	3207(81)90073-2.
1444 1445	001	
1445	585	OECD, 2003. Environmental Indicators. Development, Measurement and Use. The
1440	586	Organisation for Economic Co-operation and Development, Paris, 37pp.
1447	500	
1449	587	Ondiviela, B., Juanes, J.A., Gómez, A.G., Samano, M.L., Revilla, J.A., 2012.
1450	588	Methodological procedure for water quality management in port areas at the
1451		
1452	589	EU level. Ecol. Indic. 13, 117–128. doi: 10.1016/ j.envsci.2013.07.001.
1453	500	Darra N.M. Nari A. Karatan W. 2010 Diak Assessment Matheda in Coonarts: A
1454	590	Parra, N.M., Nagi, A., Kersten, W., 2018. Risk Assessment Methods in Seaports: A
1455	591	Literature Review. Publications of the Hazard Project 24:2018.69 pp.
1456		
1457	592	Petrosillo, I., Vassallo, P., Valente, D., Mensa, J.A., Fabiano, M., Zurlini, G., 2010.
1458	593	Mapping the environmental risk of a tourist harbor in order to foster
1459	594	environmental security: objective vs. subjective assessments. Mar. Pollut. Bull.
1460	595	60, 1051–1058. https://doi.org/10.1016/j.marpolbul.2010.01.021.
1461		
1462		
1463		
1464		
1465		
1466		
1467		
1468		
1469		
1470		
1471		
1472		
1473		
1474		
1475		


1476 1477		
1478	596	PIANC, 2011. Towards a Sustainable Waterborne Transportation Industry.
1479	590 597	EnviCom Task Group 2. September 08, 2011.
1480 1481	001	
1482		
1483	598	PIANC, 2019. A Practical Guide to Environmental Risk Management (ERM) for
1484	599	Navigation Infrastructure Projects. EnviCom WG 175. October 24, 2019.
1485 1486		
1487		
1488	600	PIANC, 2020. Climate Change Adaptation Planning for Ports and Inland
1489	601	Waterways. EnviCom WG 178. January 09, 2020.
1490 1491		
1492	600	DIANC 2006 Environmental Diak Assessment of Dradaing and Dianasal
1493	602 603	PIANC, 2006. Environmental Risk Assessment of Dredging and Disposal Operations. PIANC Secretariat General, Brussels.40 pp.
1494	000	Operations. TriAno Occietanat Ceneral, Brassels.40 pp.
1495 1496	604	Puig, M., Wooldridge, C., Casal, J., Darbra, R.M., 2015. Tool for the identification
1497	605	and assessment of Environmental Aspects in Ports (TEAP). Ocean Coast.
1498	606	Manag. 113, 8–17. doi:10.1016/j.ocecoaman.2015.05.007
1499 1500	607	Ronza, A., Carol, S., Espejo, V., Vílchez, J.A., Arnaldos, J., 2006. A quantitative
1500	608	risk analysis approach to port hydrocarbon logistics. J. Hazard. Mater. 128 (1),
1502	609	10e24. doi:10.1016/j.jhazmat.2005.07.032.
1503		
1504 1505	610	Samhouri, J., & Levin, P.S., 2012. Linking land- and sea-based activities to risk in
1505	611 612	coastal ecosystems. Biol. Conserv. 145, 118–129. doi:
1507	612	10.1016/j.biocon.2011.10.021
1508	613	Smith, A.D.M., Fulton, E.J., Hobday, A.J., Smith, D.C., Shoulder, P., 2007.
1509 1510	614	Scientific tools to support the practical implementation of ecosystem-based
1511	615	fisheries management. ICES J. Mar. Sci. 64, 633–639.
1512	616	doi:10.1093/icesjms/fsm041
1513 1514	617	Steinberg, P.D., Airoldi, L., Banks, J., Leung, K.M.Y., 2016. Introduction to the
1514	618	special issue on the World Harbour Project. Reg. Stud. Mar. Sci., 8 (2), 217-
1516	619	219. doi:10.1016/j.rsma.2016.10.001
1517		
1518 1519	620 621	Strain E, Alexander K, Kienker S, Morris R, Jarvis R, Coleman R, Bollard B, Firth L,
1520	622	Knights A, Grabowski J. 2019.Urban blue: a global analysis of the factors shaping people's perceptions of the marine environment and ecological
1521	623	engineering in harbours. SciTotal Environ 658:1293–1305.
1522	624	https://doi.org/10.1016/j.scitotenv.2018.12.285
1523 1524		
1525	625 626	UNCTAD, 2012. Review of Maritime Transport 2012. United Nations. New York
1526	626	and Geneva. United Nations.196 pp.
1527 1528	627	UNCTAD, 2017. Review of maritime transport 2017. United Nations Conference on
1529	628	Trade and Development Review. New York and Geneva.130 pp.
1530		
1531		
1532 1533		
1534		


1535 1536	
153762915386301539631	UNEP-WCMC, 2016. World Database on Protected Areas. United Nations Environment World Conservation Monitoring Centre - World Commission on Protected Areas (https://www.protectedplanet.net/).
1541         1542       632         1543       633         1544       634	United Nations, 2015. Transforming our world: the 2030 Agenda for Sustainable Development. General Assembly 70 Session, 16301 (October), 1–35. doi:10.1007/s13398-014-0173-7.2
1545 1546 <b>635</b> 1547 <b>636</b> 1548	US National Geospatial-Intelligence Agency, 2015.World Port Index, Pub 150. 250 pp.
1549         637           1550         638           1551         639           1552         640           1553         640	Valdor, P.F., Gómez, A.G., Ondiviela, B., Puente, A., Juanes, J.A., 2016. Prioritization maps: the integration of environmental risks to manage water quality in harbor areas. Mar. Pollut. Bull., 111 (1–2) 57-67.doi: 10.1016/j.marpolbul.2016.07.028
1554         641           1555         642           1556         643           1557         643           1558         644	Valdor, P.F., Puente, A., Gómez, A.G., Ondiviela, B., Juanes, J.A., 2017. Are environmental risk estimations linked to the actual environmental impact? Application to an oil handling facility (NE Spain). Mar. Pollut. Bull. 114, 941– 951. doi:10.1016/j.marpolbul.2016.10.078
1559         1560       645         1561       646         1562       647         1563       648         1564       649         1565       650         1566       1567         1567       651         1568       652         1569       653         1570       1571         1572       1573         1574       1575         1576       1577         1578       1579         1580       1581         1582       1583         1584       1585         1586       1587         1588       1589         1590       1591         1592       1593	<ul> <li>Valdor, P.F., Gómez, A.G., Juanes, J.A., Kerléguer, C., Steinberg, P., Tanner, E., MacLeod, C., Knights, A.M., Seitz, R.D., Airoldi, L., Firth, L.B., Crowe, T., Chatzinikolaou, E., Smith, A., Arvanitidis, C., Burt, J.A., Brooks, P.R., Ponti, M., Soares-Gomes, A., Ovejero, A., Méndez, G., 2019. A global atlas of the environmental risk of marinas on water quality. Mar. Pollut. Bull. 149, 110661. doi:10.1016/j.marpolbul.2019.110661</li> <li>Yin, J., Falconer, R.A., Che, Y., Probert, S.D., 2000.Water and sediment movements in harbours. Appl. Energy 67, 341e352. Pll: S0306-2619(00)00030-1.</li> </ul>















Parameters Indicators



General dat	a
Harbour's n	
Postal addr	ess:
Code:	
City:	
Country: web:	
phone:	
e-mail addr	ess:
Hydromorp	hological characteristics:
Entrance le	ngth (in meters):
-	al range (in meters):
	oth (in meters):
-	rbour entrance (in meters):
Human pres	trade vessels visits per year:
	n activities are developed in the harbour:
I Fuel oil ar	nd diesel oil supplies
I Major rep	air services
Dangerous	s/hazardous goods handling
Frequency of	of dredging operations:
Continual	
I Periodic	
I No dredgi	ng
Environmer	ntal management
Please, speci implemente	Environmental Standard: cify what kind of environmental standards (international certifications) are ed in the marina: n environmental measures are implemented in the harbour: s:
Garbage o	lisposal
Dirty balla	ast management
0 Waste ma	inagement
Bilge man	agement, Sewer Pump-Out
0 Oil manag	jement
Specify any	other environmental measure or instrument implemented in the harbour:

#### Application scope

- 1. Access to GoogleEarth: <u>https://www.google.es/intl/es/earth/</u>
- 2. Introduce the name of the harbour in the seeker.
- 3. Using Add -> Add a polygon: draw the water surface where port activity takes place.
- 4. Save the polygon as a .kmz and send it with this questionnaire filled out to: <a href="https://www.xxxx.autican.es">xxxxx.autican.es</a>

Paloma F. Valdor: Conceptualization, Methodology, Data curation, Resources, Formal analysis, Visualization, Writing - Original Draft, Writing - Review & Editing Aina G. Gómez: Conceptualization, Methodology, Supervision, Writing - Original Draft, Writing - Review & Editing Peter Steinberg: Funding acquisition, Writing -Review & Editing Edwina Tanner: Resources, Data curation, Writing - Review & Editing Antony M. Knights: Resources, Data curation, Writing - Review & Editing Rochelle D. Seitz: Resources, Data curation, Writing - Review & Editing Laura Airoldi: Resources, Data curation, Writing - Review & Editing Louise B. Firth: Resources, Data curation, Writing - Review & Editing Christos Arvanitidis: Resources, Data curation, Writing - Review & Editing Massimo Ponti: Resources, Data curation, Writing - Review & Editing Eva Chatzinikolaouf: Resources, Data curation, Writing - Review & Editing Paul R. Brooks: Resources, Writing - Review & Editing Tasman P. Crowe: Resources, Data curation, Writing - Review & Editing Alison Smith: Resources, Data curation, Writing - Review & Editing Gonzalo Méndez: Resources, Data curation, Writing - Review & Editing Aida Ovejero: Resources, Data curation, Writing - Review & Editing Abilio Soares-Gomes: Resources, Data curation, Writing - Review & Editing John A. Burt: Resources, Data curation, Writing - Review & Editing Catriona MacLeod: Resources, Data curation, Writing - Review & Editing José A. Juanes: Corresponding author, Conceptualization, Methodology, Funding acquisition, Supervision, Project administration, Writing - Review & Editing