Faculty of Science and Engineering

School of Geography, Earth and Environmental Sciences

2017-12-17

Active normal faults and coupled landscape response: bedrock variability in the southern Gulf of Corinth, central Greece

Zondervan, JR

http://hdl.handle.net/10026.1/16311

All content in PEARL is protected by copyright law. Author manuscripts are made available in accordance with publisher policies. Please cite only the published version using the details provided on the item record or document. In the absence of an open licence (e.g. Creative Commons), permissions for further reuse of content should be sought from the publisher or author.

Active normal faults and coupled landscape response: bedrock variability in the southern Gulf of Corinth, central Greece

Jesse R. Zondervan^{1,2}, Alexander C. Whittaker¹, Rebecca E. Bell¹, Stephen E. Watkins¹, Sam A.S. Brooke¹

Fluvial erosion processes control landscape response to climatic and tectonic signals and its propagation into sedimentary basins. Considerable effort has gone into quantifying and modelling the effect of changes in uplift rates on fluvial erosion in bedrock rivers. However, current landscape models, based on stream power, tend to ignore the effects bedrock variability.

The lack of available data relating rock strength to bedrock erodibility in fluvial settings has limited our ability to explore this question. Recent attempts at modelling to resolve this issue rely on indirect or theoretical rock strength properties. An alternative approach requires field measurements of rock strength together with geomorphological and tectonic constraints to quantify the effect of rock strength on river evolution.

The Gulf of Corinth, central Greece, is one of the fastest extending rifts in the world and tectonic boundary conditions are well constrained. We (1) review published constraints on uplift along the active normal faults on the southern coast of the Gulf, and project uplift away from the faults into three catchments using a viscoelastic dislocation model; (2) test how channel width and slope vary in these rivers upstream of the active faults, and we use this data to estimate the distribution of stream power down-system; (3) systematically measure rock strength, using a Schmidt hammer, to constrain its effect on river response to uplift.

All the rivers have knickpoints upstream of the active faults and we show they are responding transiently to active faulting. By assuming that our derived uplift rate equals stream power-driven erosion rate we calculate the erodibility, k, of bedrock. We demonstrate that stream powers in rivers crossing faults in the southern Gulf of Corinth correlate with rock strength and derive a non-linear power relationship between bedrock erodibility k and Schmidt hammer rebound. These findings highlight the need to incorporate bedrock variability into stream power erosion models.

¹ Department of Earth Science & Engineering, Imperial College, South Kensington, London SW7 2AZ. UK

² now at: School of Geography, Earth and Environmental Sciences, Plymouth University, Plymouth PL4 8AA

^{*}corresponding author: jesse.zondervan@plymouth.ac.uk